

SONY®

NTSC/PAL

DVCAM Drive

DRV-1000/1000P

*Full DV Editing with
the DRV-1000/1000P
DVCAM Drive and
a Video Capture Board*



With the increase of digital video acquisition in both consumer and professional markets, the demand for PC-based editing is growing rapidly. The Sony DRV-1000/P DVCAM Drive has been developed so that material shot on DV and DVCAM sources can be edited in a low-cost PC-based editing system. The DRV-1000/P has been specifically designed to fit directly into a standard PC 5.25-inch disk drive bay, forming a complete, innovative and low-cost editing system.



DRV-1000/1000P

DVCAM Format


The DRV-1000/P provides the superb picture quality and professional reliability of the DVCAM format. It offers excellent

audio quality and can record signals in both 48 kHz/16-bit and 32 kHz/12-bit modes. It is also capable of playing back DV format (SP mode only) tapes.

Compact Size and PC Compatible Design

The DRV-1000/P is designed to fit in a standard 5.25-inch disk drive PC bay. The cassette compartment slides in and out of the outer chassis to make insertion and ejection of the mini cassette easy. Its off-white color and

simple design make it suitable for PC operating environments.



Full DV Editing

The DRV-1000/P is equipped with i.LINK (DV IN/OUT) connection, which is based on the i.LINK (IEEE1394). With a single cable connection to this 4-pin DV IN/OUT connector, a DV signal* is transmitted to and downloaded from the PC system (AV/C** command signal can also be received by this single DV cable). This means that a full DV editing system can be configured by using the DRV-1000/P and a 3rd party capture board, interfaced via a DV cable.

*DV signal: compressed digital video/audio signals

**AV/C command signal: VTR command signals defined in the DV IN/OUT protocol, DRV-1000/P can accept basic VTR functional commands.

Other Features

- DC Power Operation
- LANC and Analog Video/Audio Output

Specifications

GENERAL

Weight:	Approx. 1.4 kg (3 lb 1 oz)
Dimensions:	149.2 (W) x 42.8 (H) x 225 (D) mm (5.87 x 1.69 x 8.86 inches)
Maximum Dimensions (unload)	149.2 (W) x 68.0 (H) x 305 (D) mm
Power Requirement:	+5V: 5A (Max) /700mA (Stop) +12V: 0.8A (Max) /130mA (loading/unloading)
Power Consumption:	+5V: 25VA (Max) +12V: 9.6VA (Max)
Operating Temperature:	5 C° - 40 C° (41°F - 104°F)
Storage Temperature:	-20 C° - 60 C° (-4°F - 140°F)
Tape Speed:	28.2mm/s. (DVCAM mode)

VIDEO

Video Signal:	EIA standards, NTSC color (for NTSC area) CCIR standards, PAL color (for PAL area)
Video Output	Composite (RCA pin) 1Vp-p, 75Ω, unbalanced, sync negative Y/C (mini-DIN 4-pin) luminance signal: 1Vp-p, 75Ω, unbalanced, sync negative chrominance signal: 286mVp-p (subcarrier burst), 75Ω, unbalanced (NTSC) 300mVp-p (subcarrier burst), 75Ω, unbalanced (PAL)

AUDIO

Audio Signals:	48kHz/16-bit, 32kHz/12-bit, 32kHz/16-bit, 44.1kHz/16bit (depending on input signals)
Output:	Phono jacks (L&R x 1)
Output Level:	327mV with 47kΩ load or more Impedance: 2.2kΩ
Digital IN/OUT:	i.LINK (DV IN/OUT) IEEE1394 based, 4-pin x 1
Other Connectors:	LANC: stereo mini-mini jack EJECT: monaural mini jack, TTL input low active (more than 100ms) DC IN: PC-standard, +5V/12V/GND
Supplied Accessories:	Operation manual (1) DV cable (4p - 4p, 50cm x 1) AV cable (x 1) Y/C video cable (x 1) Mounting Screw (x 4)



Front Panel



Rear Panel

Features and specification subject to change without notice.
Sony, DVCAM and i.LINK are trademarks of Sony corporation.

Distributed by

Sony Electronics Inc. (USA)
Headquarters
1 Sony Drive
Park Ridge, NJ 07656
www.sony.com/professional