


GVM Monitors



13" GVM-1311Q

(NTSC/PAL/SECAM/NTSC_{4,43})

- Multiple input facility with audio
- Multiscan capability; horizontal 15 kHz–36 kHz, vertical 50 Hz–100 Hz
- A high resolution of 600 TV lines/1024 x 768 pixels
- Can be used with IBM PC with CGA/EGA card, IBM PS/2, and Apple Macintosh II color mode
- 8/16/64-color and monochrome display capability
- VGA Audiosize function in RGB A mode
- Horizontal and vertical size/shift controls in RGB mode
- Slot type RGB input for future I/F board
- Sub picture control for RGB mode
- Built-in speaker and earphone jacks for audio monitoring
- Minimizes VLF (Very Low Frequency)/ELF (Extreme Low Frequency) interference

Optional Accessories:

RM-787 Wired Remote Control Unit
SU-552 Tilt Swivel Stand

Specifications for Color Video Monitors



SPECIFICATIONS		MODEL		GVM-1311Q	GVM-1316TSQ	GVM-2020	
Video signals		EIA 525 lines, 60 fields/CCIR 625 lines, 50 fields (switching of EIA to CCIR or vice versa is automatically done)			EIA 525 lines, 60 fields		
Color system		NTSC/PAL/SECAM/NTSC _{4.43} ³ (automatically selected)			NTSC		
Picture tube		14" Super Fine Pitch Trinitron CRT, visible picture size 13" measured diagonally, AG pitch 0.25mm			54.5cm (21"), Fine Pitch Trinitron tube, visible picture size 50.6cm (20") measured diagonally, 100° deflection		
Horizontal resolution		600 TV lines (Video inputs) 1024 x 768 pixels (RGB inputs)			560 TV lines (Video inputs) 720 x 480 pixels (RGB inputs)		
Scanning frequency		Horizontal: 15 kHz to 36 kHz Vertical: 50 Hz to 100 Hz					
Audio power output		0.5W, 8Ω, monaural			2.0W with built-in speaker		
Power requirements		AC-120, 50/60 Hz					
Power consumption		95W		103W		160W	
Dimensions (WHD)		379 x 365 x 411mm (15" x 14 ³ / ₈ " x 16 ¹ / ₄ ")		379 x 365 x 421mm (15" x 14 ³ / ₈ " x 16 ⁵ / ₈ ")		510 x 475 x 510mm (20 ¹ / ₈ " x 18 ³ / ₄ " x 20 ¹ / ₈ ")	
Weight		Approx. 37 lb. 8 oz. (17 kg.)		Approx. 40 lb. 13 oz. (18.5 kg.)		Approx. 66 lb. 2 oz. (30.0 kg.)	
VIDEO	IN	LINE A	BNC	Composite 1.0Vp-p, sync negative, Automatic 75Ω termination* ²		Composite 1.0Vp-p, sync negative, Automatic 75Ω termination* ² Y/C: Y (Luminance signal): 1.0Vp-p, sync negative, 75Ω switchable C (Chrominance signal): NTSC: 0.286Vp-p, 75Ω, switchable PAL: 0.3Vp-p, 75Ω, switchable	
		LINE B* ¹	Mini DIN 4-pin	—			
			BNC	—			
	OUT	LINE A	BNC	Loop-through			
		LINE B	Mini DIN 4-pin	Loop-through			
			BNC	—			
RGB	IN	RGB A	9-pin D	Analog RGB: 0.7Vp-p, positive, 75Ω Digital RGB: TTL level, positive Sync: Analog level: 1.0Vp-p, negative, 75Ω Sync on Green: 0.3Vp-p, negative, 75Ω TTL level: negative/positive		Analog RGB: 0.7Vp-p, positive, 75Ω Digital RGB: TTL, positive Sync: Composite sync: 1.0Vp-p, negative, 75Ω H/V separate sync: TTL, negative/positive	
		RGB B	25-pin D	Analog RGB: 0.7Vp-p, positive, 75Ω Digital RGB: TTL level, positive Sync: Analog level: 1.0Vp-p, negative, 75Ω Sync on Green: 0.3Vp-p, negative, 75Ω TTL level: negative/positive		—	
			BNC	—		RGB: 0.7Vp-p, positive, 75Ω Sync: Composite sync: 1.0Vp-p, negative, 75Ω H/V separate sync: TTL, negative/positive Sync on Green: 0.3Vp-p, negative, 75Ω	
	OUT	LINE A	Phono	— 5 dBs, high impedance			
		LINE B	Phono	— 5 dBs, high impedance			
		LINE B	Phono	— 5 dBs, impedance > 47 kΩ		— 5 dBs, high impedance	
		Loop-through					
		Loop-through					
		Touch screen for GVM-1316TSQ					
External computer interface		RS232C port, D-sub 25-pin Baud rate: 9600 bps, Communication Protocol: Binary					
Material		Glass (non-glare), 3.2mm thick					

*¹The Y/C input has priority over the composite input.

*²75Ω termination is automatically set to OFF when connection is made to the OUT connector.

*³The NTSC_{4.43} system refers to an NTSC color system in which the subcarrier frequency is modified to 4.43 MHz.