





Power Save software

Hand-held Monitor ♦ 2.5-inch color TFT LCD monitor Brightness control capability Monitor hood for a field production use LCD backlight OFF capability:

Remote Control of Camcorder Functions

- ♦ REC Start/Stop, REC Review (with auto videolight on/off if attached)
- Zoom control*
- ◆ TAKE, NG marking for ClipLink™ operation
- * Requires lens with remote zoom capability



Supplied Accessory

- ♦ CCA-7-7A Camera Cable
- Strap for Remote Control Unit
- Instruction Manual

High Quality Microphone Omni-directional type for superior sound quality Volume control function ◆ Lavaliere Microphones (ECM-44BC/55BC/77BC) can be connected instead of the attached microphone



General

Signal input: Power consumption: Dimensions:

Operation temperature:

Cable length:

Monitor Display:

Microphone

Connector:

Directivity:

Composite (RM-VJ1: NTSC, RM-VJ1P: PAL) 3 W (at operation), 1.3 W (backlight off) 261(H) x 77.4(W) x 32.5(D) mm (w/o projections) (10 3/8 x 3 1/8 x 1 5/16 inches)

240 g (8 oz)


0°C to 40°C (32°F to 104°F)

7 m (20 ft) (CCA-7-7A only)

2.5-inch TFT LCD, 180K dot (NTSC/PAL)

4-pin (equivalent to ECM-77BC)

Omni-directional



© 1999 Sony Corporation. All rights reserved. Reproduction in whole or in part without written permission is prohibited. Features and specifications are subject to change without notice. All non-metric weights and measures are approximate. DVCAM and ClipLink are trademarks of Sony Corporation. Sony is a registered trademark of Sony Corporation. All other trademarks are the property of their respective owners.

Distributed by

Printed in Japan MK7266V1OHB99JAN