


XGA

VPL-PX31 SUPERBRIGHT  (00-0525)
Portable and Install LCD Projector

\$10,500.00

ON-TIME SUPPORT (V-2028)

High Brightness: **2800** ANSI lumens via a 200W UHP Lamp. Native XGA Resolution 1024 x 768. Silent Fan Noise: 34dB . The VPL-PX31 uses Sony's 3D gamma correction. HDTV Ready (480/60p, 575/50p, 1080/50i, 1080&1250/50i, 720/60p, 720/50p): Flexible Input Capability: Composite, S Video, component, YCbCr, YPbPr, and RGB. New RGB Enhancer for Crisp RGB Images. Digital Keystone Correction. Advanced APA Function. USB Hub Function for Networking connectivity. Sony's "Projector Station" software. Control the computer mouse functions via the projector's remote. New Help Function for Simple User Operation. Digital Zoom. Projector Station Software allows computers with USB ports to control the projector settings and inputs, as well as open files on your PC via the projector remote control. Laser Pointer: Built in to the projector remote control. Bi-level Lamp Power Selector: Lamp Mode can be set to High or Low depending on ambient light conditions. The lamps low setting will extend lamp life by approximately two times. Low level light output is approximately 2100 ANSI lumens. Auto Input Search: When Auto Input SEL is "ON", the VPL-PX31 searches the input channels and skips "NO INPUT" channels. Discrete Input Selection: The video and S-video inputs can be discretely selected. Variable Audio Output. Input A-5 BNC RGB/Component, 15-pin HD VGA Connector, Digital RGB, USB, Mouse, Audio, -Input B-15-pin HD VGA Connector, Mouse, Audio, -Video Input, -S-Video, Composite Video, 2-channel Audio. Video Output -15-pin HD VGA Connector, Audio, -RS-232 Port, Control S, Digital Keystone Correction , Digital Zoom



Supplied accessories:

RM-PJ610 Remote Commander Unit, Monitor cable SMF-410, Mouse cable (2m): SIC-S21 (for serial) , SIC-S22 (for PS/2), Audio Visual cable (1.5m), USB Cable Atype – B type (2m), USB Application, Software "Projector Station" vers. 2.0, AA battery (x 2), Lens Cap, Strap for remote commander, Air Filter, AC power cord, Operating Manual

Optional Accessories:

LMP-P201 User replaceable lamp, VPLL-ZM31 Short focus zoom lens, VPLL-FM21 Fixed short focus lens, VPLL-ZM101 long focus zoom lens, PSS-610//A Projector ceiling suspension support, PSS-20 Ceiling suspension support extension pole, RM-PJ10 Infrared remote control receiver extended, PC-3000 Signal interface switcher, SIC-20A / 20B / 20C / 21 / 22, SMF-400 D-sub HD 15pin - 5 BNC cable, SMF-401 D-sub HD 15pin - D-sub HD 15pin, MACVIEWLX Macintosh® computer to VGA™ adapter, RCC-5G / 10G / 30G 9 pin remote cables for RS-422A, VLC-P5 soft rolling case, VLC-P20 ATA approved case, VLC-D1 dust cover.

Dimensions: **13 3/8 (w) x 5 5/8 (h) x 13 1/4 (d) inches (339 x 142 x 335 mm)**

Weight: **15lbs. 14oz.**