

Key Features

- High Definition TV Tuner for Hotel VOD applications
- Pro:Idiom™ compliant
- MTI Port for interface with Pay-Per-View systems
- Compatible with: LodgeNet, OnCommand, nStreams, Guest-Tek, others
- Channel Mapping of display inputs
- Stand-Alone and Lodging Mode



Features

Video

Screen Modes (16:9): Letterbox

Screen Modes (4:3): Yes

Specifications

Video

Format(s) Supported: MPEG-2 4:2:0, SD MP@ML and HD MP@HL (transport and program streams), MPEG-4* / H.264* / Windows Media 9*

Tuner: ATSC, NTSC, QAM

Resolution: NTSC (480i), PAL (576i)*, 480p, 576p*, 720p, 1080i

Audio

Format(s) Supported: MPEG-2 (layer 1 & 2), AC-3, MP3 (MPEG-1 layer 3)*, LPCM* / PCM* / AAC* (19 Mbps Maximum data rate)

Protocols: Single channel, Dual Mono, Stereo, Downmix of 5.1 channels to 2 channels

Inputs and Outputs

Analog Audio Output(s): L/R RCA Jack

RF Connection Input(s): (75 Ohms) NTSC, ATSC, QAM

Data Port: RJ12 - Serial Communication Out

HDMI™ Connection Output(s): 1 (one)

Digital Audio Output(s): SPID Digital Audio (5.1 Surround)

DC-In: 12v

Supplied Accessories

AC Adapter (12v DC)

RJ12 to Serial Control Cable: RS232 and Control-S. (RJ12 connection to SP35; 9-Pin Serial for monitor RS232; 3.5mm minijack for monitor Control-S.)

Mounting Brackets

UPC Code: 027242233232



Please visit the Dealer Network for current information at www.sony.com/dn