

Key Features

- High Definition Digital Signage
- Flexible HD Formats (MPEG2, MPEG4, H.264, WM9HD)
- UDP Multicast support for efficient bandwidth management
- Group Control Software / Playlist control included
- Dolby Digital 5.1 Surround Sound
- Internal Design for clean installation



Key Technologies

Streaming content delivery IP Based, real time decoding (20 Mbps)

Multi format HD support MPEG4/2, H.264, WM9

Digital Audio surround sound support 5 Channels

IP based display control IP to RS232 control

FW40 Commander Software Device Configuration: Grouping, Scheduling, Playlist Creation, Content Management

Firmware Update Capability In-circuit

Specifications

UPC Code: 027242232983

Video

Format(s) Supported: MPEG2 480i, 480p, 720p, 1080i (supports MPEG2-TS and RTP over UDP/IP)(system layer protocol for lip-synch); MPEG4; MPEG4?H.264 (up to 1080i); WM9HD (up to 1080i)

Audio

Format(s) Supported: MP3, PCM, AAC, Dolby Digital 5.1

Inputs and Outputs

USB Port(s): USB2.0 external option

Input(s): RS-232C internal

Audio/Video Output(s): SPDIF external coaxial; Component internal, up to 1920 x 1080i @ 60 Hz; RGB internal, up to 1600 x1200

Ethernet Port: LdAN 10/100BASE-T

Power

Power Consumption: 6 Watts

Power Requirements: Input Voltage internal, 5V/3V

Dimensions

Weight: 0.5 lbs

Measurements: 122.5 x 20 x 82 mm

Operating Conditions

Operating Temperature: 0 to 40 C

Operating Humidity: 80% maximum relative humidity, non-condensing

Software

Supplied Software: Embedded Web Server, Display Commander, Ziris Manage

Networking/Modem

Ethernet Protocol: Internet IP, TCP, UDP, ICMP, ARP, DHCP, HTTP, FTP, IGMP

Graphics

Format(s) Supported: JPEG, TIF, GIF, PNG, BMP, HTML

Optional Accessories

FWD-42-PV1

FWD-40LX1

FWD-40LX2

FWD-32LX1R

FWD-32LX2

FWD-50PX2



Please visit the Dealer Network for current information at www.sony.com/dn