

Key Features

- High Definition Digital Signage
- 60GB Local Media Storage
- Support for up to 5 layers of media
- Flexible HD Formats (MPEG2, MPEG4, H.264, WM9HD)
- UDP Multicast support for efficient bandwidth management
- Group Control Software / Playlist control included
- Dolby Digital 5.1 Surround Sound
- Internal Design for clean installation



Image not final

Key Technologies

Streaming content delivery IP Based, real time decoding (20 Mbps)

Multi format HD support MPEG4/2, H.264, WM9

USB Supports external storage or content sync/update

SRS support 5 Channels

IP based display control RS232 protocol

FW40 Commander Software Device Configuration: Grouping, Scheduling, Playlist Creation, Content Management

Firmware Update Capability In-circuit

Specifications

Video

Format(s) Supported: WM9HD (up to 1080i)

Audio

Format(s) Supported: AAC

Inputs and Outputs

USB Port(s): USB2.0 external option

Input(s): RS-232C internal

Audio/Video Output(s): RGB internal, up to
1600 x1200

Ethernet Port: LdAN 10/100BASE-T

Power

Power Consumption: 6 Watts

Power Requirements: Input Voltage internal,
5V/3V

Dimensions

Weight: 1.0 lbs

Measurements: 122.5 x 20 x 82 mm

Operating Conditions

Operating Temperature: 0 to 40 C

Operating Humidity: 80% maximum relative
humidity, non-condensing

Software

Supplied Software: Embedded Web Server,
Display Commander, Ziris Manage

Networking/Modem

Ethernet Protocol: Internet IP, TCP, UDP, ICMP,
ARP, DHCP, HTTP, FTP, IGMP

Graphics

Format(s) Supported: HTML

Optional Accessories

FWD-42PV1

FWD40LX1

FWD-40LX2

FWD-32LX1R

FWD-32LX2

FWD-50PX2

UPC Code: 027242233324



Image not final

Please visit the Dealer Network for current
information at www.sony.com/dn