

Key Features

- Internal High Definition TV Tuner for Hotel VOD applications
- Pro:Idiom™ compliant
- MTI Port for interface with Pay-Per-View systems
- Compatible with: LodgeNet, OnCommand, nStreams, Guest-Tek, others
- Channel Mapping of display inputs
- Stand-Alone and Lodging Mode



ICS-SP30 Internal High Definition TV Tuner for Hotels

Features

Video

Screen Modes (16:9): Letterbox Screen Modes (4:3): Yes

Specifications

Audio

Format(s) Supported: MPEG-2 (layer 1 & 2), AC-3, MP3 (MPEG-1 layer 3)*, LPCM* / PCM* / AAC* (19 Mbps Maximum data rate)

Protocols: Single channel, Dual Mono, Stereo, Downmix of 5.1 channels to 2 channels

Video

Format(s) Supported: MPEG-2 4:2:0, SD MP@ML and HD MP@HL (transport and program streams), MPEG-4* / H.264* / Windows Media o*

Tuner: ATSC, NTSC, QAM

Resolution: NTSC (480i), PAL (576i)*, 480p, 576p*, 720p, 1080i

Inputs and Outputs

Analog Audio Input(s): 3.5mm minijack (shared between Composite and S-Video)

Analog Audio Output(s): 3.5mm minijack (line level out)

Composite Video Input(s): One

Control-S Input(s): One

RF Connection Input(s): (75 Ohms) NTSC, ATSC, QAM

S-Video Input(s): One Data Port: RJ12 - MTI Port

HDMI™ Connection Output(s): One

Digital Audio Output(s): SPID Digital Audio (5.1 Surround)

UPC Code: 027242233225