

HME DX200™ vs. Telex BTR-24 & ~~BTR600~~

Feature	DX200	BTR-24	BTR600
RF Frequency Range	2.4-2.4835 GHz FHSS	2.4 GHz 802.11b (2.4 - 2.4835 GHz) 11 Channels DSSS	MHz Controlled
Base Transmit Power	100 mW	200 mW	Typical
License-Free Operation	YES	YES	
Antenna and Channel Diversity	YES	YES	
Automatic Frequency Selection	YES	YES - ClearScan, 11 Channels	
Wireless Isolated Channel	YES	YES	
Simultaneous 2-Wire and 4-Wire Operation	YES	NO	YES
RTS® and ClearCom® 2-Wire Interface Support	YES	YES	(Standard)
Remotely "Unlatch" Beltpacs from Transmitting	YES	NO	NO
Beltpac Transmit Power	100 mW No SAR Test	70 mW (SAR TEST APPROVED)	
Voice Prompts	YES	YES	
ISO+ Mode	YES	YES	
Internal Beltpac Antennas	YES	YES	
Low Battery Indication	LED Blink & Voice Prompt	LED Only	LED Only
Beltpac Weight	7.4 oz.	12 oz	

Continued.....

Feature	DX200	BTR-24
Number of Audio Channels	1	3
Programmable Buttons	NO	YES
Base Station Size	1 RU Wide by 1 RU Tall	1/2 RU Wide by 1 RU Tall
Base Station Weight	9 lbs 2 oz	2 lbs 11 oz
Base Station Battery Operation	NO - DX200 YES - DX100	YES - 8-10 Hrs
Type of Base Station Battery	6 AA	LiON Recharge
System P/N Available with Case	NO	YES
SAR Test	NO	YES
Beltpack XLR Connector	NO	YES
Rack Mtg & Wall Mount HDW Included	NO	YES
Frequency Response	200 - 3500 Hz	400 - 5500 Hz
Warranty	2 Years	3 Years