

Cinema-quality at home.

The ViewSonic® Cine1000 home theater projector lets your family WATCH WIDESCREEN TV AND DVDs WITHOUT A BULKY TV in your entertainment center. The innovative six segment color wheel fills your room with rich, lifelike images. In addition the 2000:1 contrast ratio and support for HD SIGNALS ENSURE YOU GET THE SHARPEST POSSIBLE DIGITAL IMAGES. Advanced video processing features such as motion adaptive deinterlacing, and 3:2 pull down deliver crisp, vivid video. Optical zoom, keystone correction and wireless remote put you in the driver's seat – in the comfort of your own living room. Get ready for revolutionary home entertainment.

Cine1000

WIDESCREEN HOME THEATER PROJECTOR

WITH DLP™ TECHNOLOGY



BRILLIANT FAMILY ENTERTAINMENT

- > **Bright in virtually any setting with 1,000 lumens**
Packs 1,000 lumens in just 7.9 lb. It's the bright choice for home theater.
- > **Supports HD signals including 720p and 1080i**
Capable of displaying HD signals as well as other video and data sources*.
- > **Easy set up and auto tuning**
Auto source detection and auto sync.
- > **The perfect image in any setting**
Digital keystone correction, short focal length and optical zoom function ensure the perfect size image in any room.
- > **Whisper-mode extends lamp life**
Extend the life of your lamp up to 4,000 hours** and reduce noise output.
- > **Ultimate flexibility with multiple inputs**
Rich connectivity with RGB, DVI-I (HDCP), component video, composite video and S-video inputs and a monitor output.
- > **Among the best warranties in the business**
Covered by a three-year parts and labor limited warranty, first-year Express Exchange® and 90-day lamp limited warranty.**



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

ViewSonic® 

the choice of professionals

Cine1000

WIDESCREEN HOME THEATER PROJECTOR WITH DLP™ TECHNOLOGY



Optional Accessories

- ATA hard shipping caseCASE-003
- Rolling soft case and laptop bagPRJ-SCA-004
- Replacement lampRLC-016
- Universal ceiling mount kitWMK-005
- Extended Express Exchange®PRJ-EE-08-03

PROJECTOR	Type	0.55" 480p Digital Micromirror Device (DLP™)
	Pixel Format	854x480 (native resolution)
	Lens	Manual zoom/manual focus
	Zoom Factor	1.2
	Keystone	Vertical ± 15°
DISPLAY	Size	43.4"-230" (diagonally)
	Throw Distance	59"-315"
	Throw Ratio	1.56-1.9:1
	Lamp	200W, 3,000 hours**
	Brightness	1,000 ANSI lumens
	Contrast Ratio	2000:1
	Aspect Ratio	16:9 (native), 4:3
INPUT SIGNAL	Video	NTSC 4.43, PAL, SECAM, HDTV (480i, 480p, 720p, 1080i)
	Frequency	F _H : 31-70kHz; F _V : 50-85Hz
COMPATIBILITY	PC	Analog: from VGA up to SXGA (scaled)
	Mac®†	Analog: up to SXGA (may require a Mac adapter)
CONNECTOR	RGB (input)	DB-15 (x1)
	DVI (input)	DVI-I (x1) – HDCP compliant
	RGB (output)	DB-15 (x1)
	Video (input)	RCA jack (x1)
	S-Video (input)	Mini-DIN 4-pin (x1)
	Component Video (input)	RCA jack (x3)
	Control	RS-232 (mini-din, 3-pin)
	Audio (input)	Mini-Jack (x1); RCA (x1)
	Audio (output)	Mini-Jack (x1)
	POWER	Voltage
Consumption		255W (typ)
CONTROLS	Basic	Standby, menu, input, reset, H/V keystone
	OnView®	Main menu (brightness, contrast, sharpness, color temperature, color saturation, color, tint, gamma, color space, reset), setup menu (H. position, V. position, keystone, aspect ratio, advance feature, reset), advanced feature menu (user color, white peaking, logo display, reset), configuration, utility, language, status (lamp mode, lamp hour reset)
OPERATING CONDITIONS	Temperature	41-95°F (5-35°C)
	Humidity	5-95% (non condensing)
NOISE LEVEL	Normal	35 dB (typ)
	Whisper Mode	33 dB (typ)
DIMENSIONS (W x H x D)	Physical (mm)	328mm x 88mm x 238mm
	Physical (in.)	12.9" x 3.5" x 9.4"
WEIGHT	Net	7.8 lb. (3.5 kg)
	Gross	14.3 lb. (6.5 kg)
REGULATIONS	UL/C-UL, FCC-B, TUV, CB, CCC	
CONTENTS	Projector, composite audio/video cable, S-video cable, RGB/DVI cable, power cable, remote control with batteries, Quick Start Guide, ViewSonic Wizard CD (with user guide), soft case	
WARRANTY	Three-year limited warranty on parts and labor, first-year Express Exchange® Service. 90-day limited warranty on lamp***	

ViewSonic® 

the choice of professionals

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

Customer Service and Technical Support: (800) 688-6688 • Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

*Optional cables required. **Running whisper-mode exclusively can extend lamp life. ***Visit ViewSonic.com for details. †Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs vary by country. See your ViewSonic representative for complete details. DLP™ is a trademark of Texas Instruments. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2006 ViewSonic Corporation. All rights reserved. [12709-00B-11/05] Cine1000-1

For more product information, visit us on the web at ViewSonic.com