

ViewSonic®

PJ1060 Projector

Conference Room Series



- **True XGA 1024 x 768 resolution**
High resolution delivers superior picture definition.
- **Professional-level 2,200 lumens**
Projects bright, brilliant images for clear viewing, even in a large, well-lit room.
- **Three-panel LCD optical engine**
Three LCD panels deliver superb picture quality for sharp, well-saturated color images.
- **Digital Keystone Correction**
Squares up the picture when projecting at an angle.
- **Picture-in-picture capability**
View video and computer data simultaneously for added utility and excitement.
- **Auto tuning**
Automatic self-tuning for perfect synchronization and optimal sharpness.
- **Industry-leading 24/7 customer support**

High-brightness multimedia projector

Professional presentations are a snap with ViewSonic's PJ1060 multimedia projector. Brilliant detail and vivid images are just two of the many reasons why it leads the XGA conference-room projection category. The PJ1060 features picture-in-picture for flexibility and Digital Keystone Correction so you can square the picture at almost any angle. And it's backed by free, convenient 24/7 technical support. The PJ1060 is perfect for use in conference rooms, auditoriums, large classrooms and religious sanctuaries. The addition of a ViewSonic wide-angle lens or long-throw lens allows you to produce excellent images from most any distance, and if you want to use a rear-screen application the PJ1060 can easily accommodate. No matter what kind of lighting or audience you're working with, you're sure to appreciate the performance of the PJ1060.



ViewSonic®
See the difference.®

ViewSonic®

PJ1060 Projector



• Two computer inputs

Connect two PCs or Macs simultaneously for dynamic meetings.

• Wireless remote control with built-in mouse and laser pointer

This offers the presenter total control, flexibility and convenience.

• Soft carry case included

• ViewSonic picture quality

Consistent brightness in the corners, sharp focus and quality from an industry leader.

• User-replaceable 190W UHB extended-life lamp

Extended lamp life up to 2,000 hours.

• Optional accessories

Short throw lens	STL-01
Long throw lens	LTL-01
Spare lamp	RLU-190-03A
Hard carry case with wheels	HC2
Wall/Ceiling mount kit	PM-1060
Extended warranty	EXT WTY-CR
48 hour Express Exchange®	EE-CR

3-PANEL LCD PROFESSIONAL LEVEL BRIGHTNESS MULTIMEDIA PROJECTOR

LCD	Type	1.3" polysilicon (x3) stripe pixel, TFT active matrix
	Pixel Format	2,359,296 (1024 x 768 x3)
	Lens	Power focus, power zoom (1:1.3x)
DISPLAY	Size	30" to 300" (measured diagonally)
	Focus Distance	1.1m~11m (3.6'~36')
	Lamp	190W UHB Compact
	Brightness	2,200 lumens
	Contrast Ratio	350:1
	Digital Keystone Correction	±15°
AUDIO	Speakers	Stereo
	Power	2W (1W + 1W)
INPUT SIGNAL	Video	RGB analog, NTSC, PAL, SECAM, S-Video
	Sync	H/V Separated (TTL)
	Frequency	Fh; 15.75/15.63Khz, 25-85Khz, Fv: 56-120Hz
COMPATIBILITY	PC	PC and compatible (from VGA up to 1280x1024 non-interlaced)
	Mac®**	Power Mac™ (up to 1280 x 1024)
CONNECTOR	RGB Input	15-pin HD Mini D-sub (x2)
	RGB Output	15-pin HD Mini D-sub (x1)
	Video	RCA x1 (composite)
	S-Video	S-Connector (separate)
	Audio	M3 stereo mini jack(x2) RCA x2 (left, right)
POWER	Voltage	AC 100-240VAC 50-50 auto switch
	Consumption	370W (typ)
USER CONTROLS	Physical	Standby on/off, menu (left, right, up, down), input, reset, mute
	Remote	Power, menu, volume +/-, mute, laser, freeze, magnify +/-, menu on, mouse on, mouse L/R, timer, input, position on, cursor, reset
	OSD	Volume, brightness, contrast, sharpness, V/H position, H-phase, H-size, color, tint, color balance, input select, keystone, video detect (AUTO, NTSC, PAL, SECAM, M-PAL), mirror, blank, startup com. speed, com. bits, timer, 7 language, auto off, start up
OPERATING	Temperature	32°F to 95°F (0°C to 35°C)
CONDITION	Humidity	10% to 85% (non-condensing)
DIMENSIONS	Physical	292mm (W) x 124mm (H) x 395mm (D)
		11.4" (W) x 4.9" (H) x 15.5" (D)
WEIGHT	Net	6.0 kg (13.2 lbs)
REGULATIONS		UL, CSA, FCC-A, CE, CB report, TUV/GS, EMC report
WARRANTY		Two-year limited warranty on parts and labor. 90-day warranty on lamp.
OTHER		DDC1, DDC2B, H/V mirror image, controllable through RS232 port*



ViewSonic Corporation's QMS/EMS has been registered to ISO 9001 & ISO 14001 by the British Standards Institution.



ViewSonic®
See the difference.®

381 Brea Canyon Road, Walnut, CA 91789 • Toll Free (866) LITEBIRD (866) 548-3247 or (909) 839-7925 • Fax (909) 444-5636 • E-mail: projectors@ViewSonic.com

Mac cable adapter included. *Software not supplied. Corporate names and trademarks stated herein are the property of their respective companies. Specifications subject to change without notice.
Copyright © 2001, ViewSonic Corporation. All rights reserved.
VSPJ1060-2_06/01_WEB_110222-00B 06/01
VS-284