

# ViewSonic®

## PJ1075 Projector

### LiteBird™ Series



- **Ultra light weight and compact**  
Packs a lot of power in only 5 pounds.
- **High brightness 1200 Lumens**  
Excellent image in lighted rooms.
- **True XGA 1024 x 768 resolution, compressed SXGA 1280 x 1024**  
Supports 1280 x 1024 with advanced compression.
- **Texas Instruments DLP™ digital light processing technology**  
Superb picture quality and color uniformity.
- **Digital keystone correction**  
Squares the picture even when projecting at an angle.
- **Picture-in-Picture capability**  
View video and computer data simultaneously for added utility and excitement.
- **PersonalTheater™ projection for movies, sports and more**  
Connect DVD, VCR and TV signals for full motion video at work or home.
- **Built in zoom & focus lens for extra flexibility and functionality**

#### PRESENT WITH CONFIDENCE IN THE OFFICE OR ON THE ROAD

Any time, any place you need to deliver an exceptional presentation ViewSonic's LiteBird PJ1075 is right there with you. The LiteBird PJ1075 raises the bar for high performance, micro-portable projectors. You'll walk into any business setting with confidence knowing the PJ1075 offers superb image quality as well as high brightness and reliability, making it easy to present even in well-lit rooms. Adjustable zoom, digital keystone correction, video picture-in-picture, long lamp life, remote control and soft carrying case make this projector your presentation solution in any setting. This projector also delivers great video and can turn any wall in your home into a big-screen home entertainment system. When you want the best, choose the 5 pound LiteBird PJ1075.



[www.LiteBird.com](http://www.LiteBird.com)

# ViewSonic® PJ1075 Projector



- **Wireless remote control**  
Offering the presenter total control, flexibility and convenience.
- **Auto Tuning**  
One-touch setup button for fast, easy sync and sharp focus.
- **Industry leading 24/7 technical and customer support**
- **Ceiling & Wall mount options available**
- **Soft carry case included for easy travel**
- **Optional accessories**  
Executive carrying case EC1  
Replacement lamp RLC-150-07A  
Ceiling/wall mount kit PM 1075  
Extended warranty EXT WTY-LB  
48 hour Express Exchange® EE-LB

Projection Distance	Image Size Range
3.3'	21" - 28"
13.1'	84" - 112"
16.4'	105" - 141"
23.0'	147" - 197"
26.2'	168" - 225"
32.8'	210" - 273"

COLOR DMD SVGA MICRO PORTABLE PROJECTOR DISPLAY

DLP	<b>Type</b> <b>Aspect Ratio</b> <b>Lens</b>	T1 0.9" XGA, Digital Micromirror Device (DLP™) 4:3 or 16:9 Manual focus and zoom F=2.88 (f=31mm)
DISPLAY	<b>Color</b> <b>Size</b> <b>Proj. Distance</b> <b>Lamp</b> <b>Brightness</b> <b>Contrast Ratio</b>	16.7 Million 21" - 273" 3.3' - 32.8' 150W, OSRAM P-VIP 1200 Lumens 450:1
AUDIO	<b>Speaker</b> <b>Power</b> <b>Frequency Response</b>	1.97" x 0.71" (DxH), Circular x1 3.0W 150Hz -14kHz
INPUT SIGNAL	<b>Video</b> <b>Sync</b> <b>Frequency</b>	RGB Analog, NTSC, PAL, SECAM H/V Separated (TTL) fh:15-80 kHz; fv:43-85 Hz
COMPATIBILITY	<b>PC</b> <b>Mac®¹</b>	PC and compatibles (from VGA up to 1024x768 non-interlaced) Power Mac™ up to 1024x768
CONNECTOR	<b>RGB</b> <b>Video</b> <b>S-Video</b> <b>Audio In/Out</b>	15-pin HD RCA x1 (composite) SVHS DIN Connector 3.5 mm Mini Stereo Plug
POWER	<b>Voltage</b> <b>Consumption</b>	AC 100-240 VAC 50/60Hz AutoSwitch 200W
CONTROLS	<b>Physical</b> <b>Remote</b>  <b>OSD</b>	Power, on/standby, menu, auto/reset, source, enter Power/Standby, reset, mute, volume +/-, PIP, menu, source, arrow up, arrow left, arrow right, arrow down, freeze, keystone, zoom, in/out, resync, enter Brightness, contrast, keystone correction, color temperature, tint (video only), color (video only), image (PC input only), tracking, frequency, H/V position, auto-image, 8 language, audio, projection [front, rear, front ceiling, rear ceiling, PIP [On/Off], lamp, exit
OPERATING CONDITION	<b>Temperature</b> <b>Humidity</b>	50°F to 104°F (10°C to 40°C) 10% to 85% (non-condensation)
DIMENSIONS	<b>Physical</b>	90mm (W) x 252mm (D) x 218mm (H) 3.5" (W) x 9.9" (D) x 8.6" (H)
WEIGHT	<b>Net</b>	2.3 kg (5.0 lbs)
REGULATIONS		FCC-B, UL, cUL, CE, TUV/GS
ACCESSORIES		Power Cord, VGA 15 Pin 1.8m Cable, S-Video Cable, RCA Video Cable, Stereo RCA to Mini Stereo (3.5mm) Audio Cable, Mini Stereo (3.5mm) to Mini Stereo Audio Cable, Remote Control, Lens Cap, Soft Carrying Case



ViewSonic Corporation's QMS/EMS has been registered to ISO 9001 & ISO 14001 by the British Standards Institution.



[www.LiteBird.com](http://www.LiteBird.com)

381 Brea Canyon Road, Walnut, CA 91789  
Toll Free (866) LITEBIRD (866) 548-3247 • (909) 839-7925  
Fax (909) 444-5636 • email: [projectors@ViewSonic.com](mailto:projectors@ViewSonic.com)