# ViewSonic PJ250 Projector

## Micro-portable, light and bright



### **Business focus-palm-size 2.2-pound projector.**

ViewSonic's PJ250 projector is light and bright, making it the **ROAD-WARRIOR'S BEST FRIEND**. This 2-pound XGA projector offers 1,000 lumens and 2000:1 contrast ratio for crystal-clear images. Capable of displaying digital and analog signals for integrated data, video and audio, the PJ250 offers the **ULTIMATE IN FLEXIBILITY**, for any presentation setting on the road or in the office. Wherever you need to be, the PJ250 projector is your ideal companion. And ViewSonic's industry leading warranty program gives you the confidence you expect in any circumstances. ViewSonic® has the best warranty and service support in the business!

### **3-Year** Parts and labor limited warranty **1-Year** Free Express Exchange®

**1-Year** Lamp warranty

And we offer free 24/7 technical support<sup>1</sup> for the life of your Product, just in case.

### **Micro-Portable Series**

### ••• Light as a feather at 2.2 lbs.

Fits easily in a briefcase when you are on the road.

- --->Bright in any setting with 1,000 lumens
- True 1024x768 XGA resolution
  Produces clear, crisp images including detailed spreadsheets.
- ••••••Vivid video images and photos

Beautiful life-like pictures with an incredible 2000:1 contrast ratio.

···
 Easy set-up and auto tuning

One-touch setup button for fast, easy sync and sharp focus.

### Supports HD signals including 480i, 480p, 720p, 1080i

Capable of displaying DVI and HD signals as well as other video and data sources.\*

- ••••>Industry-leading one-year lamp warranty Extended-life lamp, warranted for a full year.\*\*
- •••• Free 24/7 customer support<sup>T</sup> Technical support wherever, whenever, just in case.
- ····**Soft carrying case included** For easy travel and extra protection.

### --->Three-year limited warranty

Covered by a three-year limited warranty and one-year Express Exchange<sup>®</sup> \*\*

### Easy-to-use remote included.





# ViewSonic PJ250 Projector

# Micro-portable, light and bright



PJ250 Distance Calculator				
Image Size (Diagonal in inches)	Height (in inches)	Width (in inches)	Throw Distance (in inches)	
36	26.1	28.8	47	
40	24	32	52	
60	36	48	78	
80	48	64	104	
100	60	80	130	
120	72	96	166	
150	90	120	195	
180	108	144	234	
200	120	160	260	

Accuracy of the calculations are +/- 5%. For additional calculations visit Viewsonic.com.

### **Optional Accessories**

Replacement lamp	PRJ-RLC-004
• DVI cable	PRJ-CBL-001
DVD component cable	PRJ-CBL-002
HDTV component cable	PRJ-CBL-003
• Extended Express Exchange <sup>®</sup>	EE-LB-02

MICRO-PORTABLE P	ROJECTOR Type	0.7" XGA DLP™	
DLF	Pixel Format Lens	1024 Horizontal x 768 Vertical (XGA)	
DISPLAY	Size Throw Distance Lamp Brightness Contrast Ratio Aspect Ratio	Manual focus 20"-245" (measured diagonally) 47"-260" (1200mm-6620mm) 120W, 2000 hour rating 1,000 Lumens 2000:1 4:3, 16:9	
AUDIO	Speakers	1 x .5 watts	
INPUT SIGNAL	Computer Video Sync Frequency	RGB analog, DVI NTSC M, NTSC 4.43, PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L), 480i, 480p, 720p, 1080i Separated F <sub>h</sub> :15–85kHz; F <sub>v</sub> :50–120Hz	
Compatibility	PC Mac*#	Analog: VGA to SXGA (scaled) Digital: VGA to XGA (scaled) Analog: to SXGA (may require Mac Adapter) Digital: to XGA (may require Mac Adapter)	
CONNECTOR	RGB DVI Video S-Video Audio	15-pin HD, D-sub cable with adapter High density 29-pin DVI-I (optional cable) RCA SVHS DIN Connector 2.5mm Mini Stereo Plug	
POWER	Voltage Consumption	100–240 VAC, 50–60Hz (universal) 150 watts (typ)	
USER CONTROLS	Physical Remote	Standby on/off, menu, enter/resync, source (data, video, and S- video), mute, volume (+, -) Standby on/off, source, page up (PU), page down (PD), volume,	
	OSD	keystone, zoom, mute, freeze, menu Display [brightness, contrast, picture adjustment, fine picture, H/V position, color, tint, sharpness, reset, gamma, color temp color sys- tem, color space, aspect, filter, projection (vertical and horizontal flip), keystone correction (H/V keystone), picture-in-picture] Setup [language, auto source, auto power off, on screen, menu position, YpbPr, background, white balance] Info [status, default, lamp timer reset, resolution, frequency, lamp timer]	
OPERATING CONDITIONS	Temperature Humidity	41° F to 95° F (5° C to 30° C) 30% to 85% (non-condensation)	
DIMENSIONS (WxDxH)	Physical	8.8" x 6.9" x 2.1" 180mm x 141mm x 45mm (excluding lens and leg)	
WEIGHT	Net	2.2 lbs (1.0 kgs)	
REGULATIONS		UL, C-UL, FCC-CLASS A, CB, CE, TUV/GS, NOM, PCT, SASSO, BSMI, PSB/S-MARK, C-TICK, CCC, EMC REPORT	
OTHER		Front and rear projection, 10 user modes. Included in box: power cord, DVI adapter, D-sub cable to DVI, composite video cable, S-video cable, remote control with batteries, lens cap, soft carrying case, Quick Start guide, user guide.	
WARRANTY	PICTURE BY	Three-year limited warranty on parts and labor, first-year Express Exchange* Service. One-year warranty on lamp.**	



# 

Catio

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

Phone (800) 888-8583 or (909) 444-8888 • In Canada (866) 262-1967 • Fax (909) 839-7922 • SalesInfo@ViewSonic.com • ViewSonic.com \*Optional cables required. \*\* Three-year limited warranty and 1-year lamp warranty available in U.S. and Canada for P1250, P1350, P1550, P1550, P1550, P1750, and P11065 projectors purchased on or after May 1, 2002. Applies to manufacturer's installed lamp only. All accessory lamps purchased separately are warranted for 90 days. Subject to terms and conditions, verification and approval. For Express Exhange program details, visit ViewSonic.com. †Excludes U.S. holidays. † Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs vary by country. See your ViewSonic Representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2004 ViewSonic Corporation. All rights reserved. [11755-008-02/04] PJ-250