ViewSonic® PJ350 Projector

Micro-Portable Series



- Ultra lightweight 3.3 pound micro-portable projector
 - Packs a lot of power in only 3.3 pounds.
- Professional level 1,100 lumens
 Get clear, bright presentations in any setting.
- True 1024x768 XGA resolution Produces clear, crisp images.
- Easy set-up and auto tuning
 One-touch setup button for fast, easy sync and sharp focus.
- Supports HDTV and DVI-I signals
 Capable of displaying DVI-I and HDTV signals as well as other video and data sources.
- RGB-out capability
 Allows you to view projected images on a monitor, too.
- Three-year limited warranty
 Covered by a three-year limited warranty and one-year Express Exchange®.*
- Industry-leading one-year lamp warranty

Extented-life lamp, warranted for a full year.*

PJ350 3.3 pound micro-portable projector.

Feel confident walking into any presentation setting with the micro-portable ViewSonic PJ350. Weighing in at just 3.3 pounds, this high-performance projector is the ultimate choice for traveling business professionals who demand excellent image quality in a lightweight, easy-to-carry package. With XGA resolution, as well as high brightness and contrast, this projector makes it easy for you to present a positive image anytime, anywhere. Digital keystone correction, DVI, zoom functions and monitor loop make the ViewSonic PJ350 projector flexible enough for any presentation setting.





ViewSonic[®]

PJ350 Projector

MICRO-PORTABLE PROJECTOR



- User-replaceable extended-life lamp 2,000 hour lamp life.
- Soft carrying case included for easy travel
- Free 24/7 customer support**
- Wireless remote control with built-in mouse and laser

This offers the presenter total control, flexibility and convenience.

- Digital keystone correction
 Squares up the picture when projecting at an angle.
- Optional accessories

Hard carrying case Replacement lamp Ceiling/wall mount kit

NICKO I OKIAD	_	O ZII VCA DI DIM
DLP	Туре	0.7" XGA DLP™
	Pixel Format	1024 Horizontal x 768 Vertical
	Lens	Manual zoom/focus F(2.2-2.4) f(28.51mm-14.21mm)
DISPLAY	Size	20" - 245" (measured diagonally)
	Throw Distance	1.0m - 12.0m (20" - 300")
	Lamp	130W OSRAM P-VIP, 2000 hour rating
	Brightness	1,100 Lumens
	Contrast Ratio	500:1
ALIDIO	Aspect Ratio	4:3, 16:9
AUDIO	Speakers	1x2W
INPUT SIGNAL	Video	RGB analog, NTSC M, NTSC 4.43, PAL (B, D, G, H, I,
		M, N), SECĂM (B, D, G, K, K1, L), HDTV
	Sync	Separated, Composite and Sync on Green (SOG)
	Frequency	F _h :15-100kHz; F _v :43-120Hz
COMPATIBILITY	PC	Analog: from VGA up to SXGA
COMPANDILITY	rc	
	.	Digital: from VGA up to XGA
	Mac ^{®†}	Analog: up to SXGA (may require Mac Adapter)
		Digital: up to XGA (may require Mac Adapter)
CONNECTOR	RGB	15-pin HD, D-sub (loop through – output only)
	DVI	High density 29-pin DVI-I
	Video	RČA
	S-Video	SVHS DIN Connector
	Audio	3.5mm Mini Stereo Plug
	Remote Mouse In	
DO\\\/EB		
POWER	Voltage	100-240 VAC, 50-60Hz (universal)
	Voltage Consumption	100-240 VAC, 50-60Hz (universal) 180W (typ)
POWER USER CONTROLS	Voltage	100-240 VAC, 50-60Hz (universal) 180W (typ) Standby on/off, menu, enter/resync, source (data, video,
	Voltage Consumption Physical	100-240 VAC, 50-60Hz (universal) 180W (typ) Standby on/off, menu, enter/resync, source (data, video, and s-video), mute, volume (+, -)
	Voltage Consumption	100-240 VAC, 50-60Hz (universal) 180W (typ) Standby on/off, menu, enter/resync, source (data, video, and s-video), mute, volume (+, -) Standby on/off, source, laser, page up (PU), page down
	Voltage Consumption Physical Remote	100-240 VAC, 50-60Hz (universal) 180W (typ) Standby on/off, menu, enter/resync, source (data, video, and s-video), mute, volume (+, -) Standby on/off, source, laser, page up (PU), page down (PD), volume, keystone, zoom, mute, freeze, menu
	Voltage Consumption Physical	100-240 VAC, 50-60Hz (universal) 180W (typ) Standby on/off, menu, enter/resync, source (data, video, and s-video), mute, volume (+, -) Standby on/off, source, laser, page up (PU), page down (PD), volume, keystone, zoom, mute, freeze, menu Display [brightness, contrast, keystone correction, color
	Voltage Consumption Physical Remote	100-240 VAC, 50-60Hz (universal) 180W (typ) Standby on/off, menu, enter/resync, source (data, video, and s-video), mute, volume (+, -) Standby on/off, source, laser, page up (PU), page down (PD), volume, keystone, zoom, mute, freeze, menu Display [brightness, contrast, keystone correction, color temperature, zoom, menu location, tint (video only),
	Voltage Consumption Physical Remote	100-240 VAC, 50-60Hz (universal) 180W (typ) Standby on/off, menu, enter/resync, source (data, video, and s-video), mute, volume (+, -) Standby on/off, source, laser, page up (PU), page down (PD), volume, keystone, zoom, mute, freeze, menu Display [brightness, contrast, keystone correction, color temperature, zoom, menu location, tint (video only),
	Voltage Consumption Physical Remote	100-240 VAC, 50-60Hz (universal) 180W (typ) Standby on/off, menu, enter/resync, source (data, video, and s-video), mute, volume (+, -) Standby on/off, source, laser, page up (PU), page down (PD), volume, keystone, zoom, mute, freeze, menu Display [brightness, contrast, keystone correction, color temperature, zoom, menu location, tint (video only), sharpness (video only), color (video only), aspect ratio,
	Voltage Consumption Physical Remote	100-240 VAC, 50-60Hz (universal) 180W (typ) Standby on/off, menu, enter/resync, source (data, video, and s-video), mute, volume (+, -) Standby on/off, source, laser, page up (PU), page down (PD), volume, keystone, zoom, mute, freeze, menu Display [brightness, contrast, keystone correction, color temperature, zoom, menu location, tint (video only), sharpness (video only), color (video only), aspect ratio, tracking, frequency, horizontal position, vertical position, signal type (RGB, component, HDTV), reset]
	Voltage Consumption Physical Remote	100-240 VAC, 50-60Hz (universal) 180W (typ) Standby on/off, menu, enter/resync, source (data, video, and s-video), mute, volume (+, -) Standby on/off, source, laser, page up (PU), page down (PD), volume, keystone, zoom, mute, freeze, menu Display [brightness, contrast, keystone correction, color temperature, zoom, menu location, tint (video only), sharpness (video only), color (video only), aspect ratio, tracking, frequency, horizontal position, vertical position, signal type (RGB, component, HDTV), reset]
	Voltage Consumption Physical Remote	100-240 VAC, 50-60Hz (universal) 180W (typ) Standby on/off, menu, enter/resync, source (data, video, and s-video), mute, volume (+, -) Standby on/off, source, laser, page up (PU), page down (PD), volume, keystone, zoom, mute, freeze, menu Display [brightness, contrast, keystone correction, color temperature, zoom, menu location, tint (video only), sharpness (video only), color (video only), aspect ratio, tracking, frequency, horizontal position, vertical position, signal type (RGB, component, HDTV), reset] Lanquage Audio [volume, bass, treble, mute,
	Voltage Consumption Physical Remote	100-240 VAC, 50-60Hz (universal) 180W (typ) Standby on/off, menu, enter/resync, source (data, video, and s-video), mute, volume (+, -) Standby on/off, source, laser, page up (PU), page down (PD), volume, keystone, zoom, mute, freeze, menu Display [brightness, contrast, keystone correction, color temperature, zoom, menu location, tint (video only), sharpness (video only), color (video only), aspect ratio, tracking, frequency, horizontal position, vertical position, signal type (RGB, component, HDTV), reset] Language Audio [volume, bass, treble, mute, stereo/mono] Projection [front, rear, front ceiling, rear
USER CONTROLS	Voltage Consumption Physical Remote OSD	100-240 VAC, 50-60Hz (universal) 180W (typ) Standby on/off, menu, enter/resync, source (data, video, and s-video), mute, volume (+, -) Standby on/off, source, laser, page up (PU), page down (PD), volume, keystone, zoom, mute, freeze, menu Display [brightness, contrast, keystone correction, color temperature, zoom, menu location, tint (video only), sharpness (video only), color (video only), aspect ratio, tracking, frequency, horizontal position, vertical position, signal type (RGB, component, HDTV), reset] Language Audio [volume, bass, treble, mute, stereo/mono] Projection [front, rear, front ceiling, rear ceiling] Lamp [lamp reminder, lamp reset]
	Voltage Consumption Physical Remote OSD	100-240 VAC, 50-60Hz (universal) 180W (typ) Standby on/off, menu, enter/resync, source (data, video, and s-video), mute, volume (+, -) Standby on/off, source, laser, page up (PU), page down (PD), volume, keystone, zoom, mute, freeze, menu Display [brightness, contrast, keystone correction, color temperature, zoom, menu location, tint (video only), sharpness (video only), color (video only), aspect ratio, tracking, frequency, horizontal position, vertical position, signal type (RGB, component, HDTV), reset] Language Audio [volume, bass, treble, mute, stereo/mono] Projection [front, rear, front ceiling, rear ceiling] Lamp [lamp reminder, lamp reset]
USER CONTROLS OPER. COND.	Voltage Consumption Physical Remote OSD	100-240 VAC, 50-60Hz (universal) 180W (typ) Standby on/off, menu, enter/resync, source (data, video, and s-video), mute, volume (+, -) Standby on/off, source, laser, page up (PU), page down (PD), volume, keystone, zoom, mute, freeze, menu Display [brightness, contrast, keystone correction, color temperature, zoom, menu location, tint (video only), sharpness (video only), color (video only), aspect ratio, tracking, frequency, horizontal position, vertical position, signal type (RGB, component, HDTV), reset] Language Audio [volume, bass, treble, mute, stereo/mono] Projection [front, rear, front ceiling, rear ceiling] Lamp [lamp reminder, lamp reset] 50° F to 104° F (10° C to 40° C) 10% to 85% (non-condensation)
USER CONTROLS	Voltage Consumption Physical Remote OSD	100-240 VAC, 50-60Hz (universal) 180W (typ) Standby on/off, menu, enter/resync, source (data, video, and s-video), mute, volume (+, -) Standby on/off, source, laser, page up (PU), page down (PD), volume, keystone, zoom, mute, freeze, menu Display [brightness, contrast, keystone correction, color temperature, zoom, menu location, tint (video only), sharpness (video only), color (video only), aspect ratio, tracking, frequency, horizontal position, vertical position, signal type (RGB, component, HDTV), reset] Language Audio [volume, bass, treble, mute, stereo/mono] Projection [front, rear, front ceiling, rear ceiling] Lamp [lamp reminder, lamp reset] 50° F to 104° F (10° C to 40° C) 10% to 85% (non-condensation) 223mm (W) x 175mm (D) x 52mm (H)
OPER. COND. DIMENSIONS	Voltage Consumption Physical Remote OSD Temperature Humidity Physical	100-240 VAC, 50-60Hz (universal) 180W (typ) Standby on/off, menu, enter/resync, source (data, video, and s-video), mute, volume (+, -) Standby on/off, source, laser, page up (PU), page down (PD), volume, keystone, zoom, mute, freeze, menu Display [brightness, contrast, keystone correction, color temperature, zoom, menu location, tint (video only), sharpness (video only), color (video only), aspect ratio, tracking, frequency, horizontal position, vertical position, signal type (RGB, component, HDTV), reset] Language Audio [volume, bass, treble, mute, stereo/mono] Projection [front, rear, front ceiling, rear ceiling] Lamp [lamp reminder, lamp reset] 50° F to 104° F (10° C to 40° C) 10% to 85% (non-condensation) 223mm (W) x 175mm (D) x 52mm (H) (8.8") x (6.9") x (2.1")
USER CONTROLS OPER. COND.	Voltage Consumption Physical Remote OSD	100-240 VAC, 50-60Hz (universal) 180W (typ) Standby on/off, menu, enter/resync, source (data, video, and s-video), mute, volume (+, -) Standby on/off, source, laser, page up (PU), page down (PD), volume, keystone, zoom, mute, freeze, menu Display [brightness, contrast, keystone correction, color temperature, zoom, menu location, tint (video only), sharpness (video only), color (video only), aspect ratio, tracking, frequency, horizontal position, vertical position, signal type (RGB, component, HDTV), reset] Language Audio [volume, bass, treble, mute, stereo/mono] Projection [front, rear, front ceiling, rear ceiling] Lamp [lamp reminder, lamp reset] 50° F to 104° F (10° C to 40° C) 10% to 85% (non-condensation) 223mm (W) x 175mm (D) x 52mm (H)
OPER. COND. DIMENSIONS WEIGHT	Voltage Consumption Physical Remote OSD Temperature Humidity Physical	100-240 VAC, 50-60Hz (universal) 180W (typ) Standby on/off, menu, enter/resync, source (data, video, and s-video), mute, volume (+, -) Standby on/off, source, laser, page up (PU), page down (PD), volume, keystone, zoom, mute, freeze, menu Display [brightness, contrast, keystone correction, color temperature, zoom, menu location, tint (video only), sharpness (video only), color (video only), aspect ratio, tracking, frequency, horizontal position, vertical position, signal type (RGB, component, HDTV), reset] Language Audio [volume, bass, treble, mute, stereo/mono] Projection [front, rear, front ceiling, rear ceiling] Lamp [lamp reminder, lamp reset] 50° F to 104° F (10° C to 40° C) 10% to 85% (non-condensation) 223mm (W) x 175mm (D) x 52mm (H) (8.8") x (6.9") x (2.1")
OPER. COND. DIMENSIONS	Voltage Consumption Physical Remote OSD Temperature Humidity Physical	100-240 VAC, 50-60Hz (universal) 180W (typ) Standby on/off, menu, enter/resync, source (data, video, and s-video), mute, volume (+, -) Standby on/off, source, laser, page up (PU), page down (PD), volume, keystone, zoom, mute, freeze, menu Display [brightness, contrast, keystone correction, color temperature, zoom, menu location, tint (video only), sharpness (video only), color (video only), aspect ratio, tracking, frequency, horizontal position, vertical position, signal type (RGB, component, HDTV), reset] Language Audio [volume, bass, treble, mute, stereo/mono] Projection [front, rear, front ceiling, rear ceiling] Lamp [lamp reminder, lamp reset] 50° F to 104° F (10° C to 40° C) 10% to 85% (non-condensation) 223mm (W) x 175mm (D) x 52mm (H) (8.8") x (6.9") x (2.1") 1.5kg (3.3 lbs) UL, FCC-B, c-UL, FDA, CE, TUV/GS, CB, BSMI, VCCI,
OPER. COND. DIMENSIONS WEIGHT REGULATIONS	Voltage Consumption Physical Remote OSD Temperature Humidity Physical	100-240 VAC, 50-60Hz (universal) 180W (typ) Standby on/off, menu, enter/resync, source (data, video, and s-video), mute, volume (+, -) Standby on/off, source, laser, page up (PU), page down (PD), volume, keystone, zoom, mute, freeze, menu Display [brightness, contrast, keystone correction, color temperature, zoom, menu location, tint (video only), sharpness (video only), color (video only), aspect ratio, tracking, frequency, horizontal position, vertical position, signal type (RGB, component, HDTV), reset] Language Audio [volume, bass, treble, mute, stereo/mono] Projection [front, rear, front ceiling, rear ceiling] Lamp [lamp reminder, lamp reset] 50° F to 104° F (10° C to 40° C) 10% to 85% (non-condensation) 223mm (W) x 175mm (D) x 52mm (H) (8.8") x (6.9") x (2.1") 1.5kg (3.3 lbs) UL, FCC-B, c-UL, FDA, CE, TUV/GS, CB, BSMI, VCCI, PSC PCT
OPER. COND. DIMENSIONS WEIGHT REGULATIONS OTHER	Voltage Consumption Physical Remote OSD Temperature Humidity Physical	100-240 VAC, 50-60Hz (universal) 180W (typ) Standby on/off, menu, enter/resync, source (data, video, and s-video), mute, volume (+, -) Standby on/off, source, laser, page up (PU), page down (PD), volume, keystone, zoom, mute, freeze, menu Display [brightness, contrast, keystone correction, color temperature, zoom, menu location, tint (video only), sharpness (video only), color (video only), aspect ratio, tracking, frequency, horizontal position, vertical position, signal type (RGB, component, HDTV), reset] Language Audio [volume, bass, treble, mute, stereo/mono] Projection [front, rear, front ceiling, rear ceiling] Lamp [lamp reminder, lamp reset] 50° F to 104° F (10° C to 40° C) 10% to 85% (non-condensation) 223mm (W) x 175mm (D) x 52mm (H) (8.8") x (6.9") x (2.1") 1.5kg (3.3 lbs) UL, FCC-B, c-UL, FDA, CE, TUV/GS, CB, BSMI, VCCI, PSC PCT Front and rear projection, 10 user modes
OPER. COND. DIMENSIONS WEIGHT REGULATIONS	Voltage Consumption Physical Remote OSD Temperature Humidity Physical	100-240 VAC, 50-60Hz (universal) 180W (typ) Standby on/off, menu, enter/resync, source (data, video, and s-video), mute, volume (+, -) Standby on/off, source, laser, page up (PU), page down (PD), volume, keystone, zoom, mute, freeze, menu Display [brightness, contrast, keystone correction, color temperature, zoom, menu location, tint (video only), sharpness (video only), color (video only), aspect ratio, tracking, frequency, horizontal position, vertical position, signal type (RGB, component, HDTV), reset] Language Audio [volume, bass, treble, mute, stereo/mono] Projection [front, rear, front ceiling, rear ceiling] Lamp [lamp reminder, lamp reset] 50° F to 104° F (10° C to 40° C) 10% to 85% (non-condensation) 223mm (W) x 175mm (D) x 52mm (H) (8.8") x (6.9") x (2.1") 1.5kg (3.3 lbs) UL, FCC-B, c-UL, FDA, CE, TUV/GS, CB, BSMI, VCCI, PSC PCT





ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.



