

ViewSonic® PJ501 Projector

Ultra-Portable SVGA Projector



Step up to the PJ501 for higher brightness.

Ideal for mobile professionals, the ViewSonic PJ501 projector offers 1,500 lumens in a lightweight 5.4-pound package. Short focal length and zoom let you set up just about anywhere. Plus, the component video feature for superior video quality and whisper-mode setting for long lamp life make the ViewSonic PJ501 projector the dependable choice for the mobile presenter in the office and on the road.

High brightness and versatility.

❖ Ideal for mobile professionals.

Packs 1,500 lumens in just 5.4 lbs. It's the bright choice for the mobile professional who demands brilliant images in virtually any setting.

❖ Crisp, clear, flexible presentations.

Offering HD capability, 1024x768 optimum resolution, and standard (4:3) and wide-screen (16:9) aspect ratios, your images are crisp and clear; your presentation options unlimited.

❖ Whisper-mode extends lamp life and reduces noise output.

Use the whisper-mode function to reduce noise output and extend the life of your lamp up to 4,000 hours*.

❖ The perfect image in any setting.

Use the one-touch setup button and auto tuning to set up quickly. Digital keystone correction, short focal length, and zoom function ensure the perfect size image in any room.

❖ Technical Support wherever, whenever you need it.

Free industry-leading 24/7 customer support,[†] just in case.

❖ The best warranty in the business.

Feel secure knowing you're covered by a three-year parts and labor limited warranty, first-year Express Exchange[®] and one-year lamp warranty.**

ViewSonic has the **best new warranty** and **service support** in the business!



3-Year parts and labor limited warranty

1-Year Free Express Exchange[®]

1-Year Lamp warranty

And we offer free 24/7[†] technical support for the life of your product, just in case.

Super bright



ViewSonic
See the difference.[®]

ViewSonic® PJ501 Projector

Ultra-Portable SVGA Projector



PJ501 Distance Calculator

Image Size (Diagonal in inches)	Height (in inches)	Width (in inches)	Throw Distance (in inches)
24	14.42	19.12	21.52
48	28.85	38.24	45.04
72	43.28	57.36	68.56
96	57.71	76.48	92.08
120	72.14	95.6	115.6
144	86.57	114.73	139.12
168	101	133.84	162.63
192	115.43	152.97	186.16

Accuracy of the calculations are +/- 5%.
For additional calculations visit ViewSonic.com.

Optional Accessories

Replacement lamp	PRJ-RLC-003
Wall/ceiling mount	PRJ-WMK-001
Rolling hard case	PRJ-HCA-001
Rolling soft case	PRJ-SCA-001
Extended Express Exchange®	EE-LB-02

ULTRA-PORTABLE SVGA PROJECTOR

LCD	Type Resolution Pixel Format Lens	3-panel 0.7" TFT active matrix LCD SVGA 800x600, compressed to 1024x768 800 horizontal x 600 vertical Manual zoom (manual x 1.2)/focus
DISPLAY	Size Throw Distance Lamp Brightness Contrast Ratio Keystone Correction Aspect Ratio	30"-300" (measured diagonally) 2.3'-29.5' (.7m-9m) 150W UHB Compact, 4,000* hour rating 1,500 lumens 400:1 ±10 degrees 4:3, 16:9
AUDIO	Speaker	1W monospeaker
INPUT SIGNAL	Computer Video Sync Frequency	RGB analog NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, PAL60, SECAM, 480i, 480p, 720p, 1080i Separated and composite Fh: 15~78kHz; Fv: 56~120Hz
COMPATIBILITY	PC Mac**	From VGA up to XGA Up to XGA
CONNECTOR	RGB Input Composite Video S-Video Component Audio In Control	15-pin HD, D-sub (x1) RCA (x1) Mini-Din 4 pin (x1) RCA (x3) RCA (x1) RS232
POWER	Voltage Consumption	100-120V AC / 220-240V AC, 50-60Hz (universal) 210W (typ), 130W (whisper-mode)
USER CONTROLS	Basic Remote OnView®	Standby on/off, menu (left, right, up, down), input, reset, mute, indicator (lamp, power, temp) Standby on/off, video, RGB, menu, keystone, position, menu select (left, right, up, down), reset, freeze, magnify (+, -, off), volume (up, down), mute, timer, auto, blank Brightness, contrast, V. position, H. position, H. phase, H. size, color balance (red), color balance (blue), aspect ratio, auto, RGB, keystone, blank, mirror, start up, volume, menu color, timer, language, auto off, sync on green
OPERATING CONDITIONS	Temperature Humidity	32°-95° F (0°-35° C) 10-85% (non-condensing)
DIMENSIONS	Physical	10.9" x 8.3" x 2.4" 277mm x 211mm x 61mm
WEIGHT	Net Gross	5.4 lbs. (2.50 kgs) 14.86 lbs. (6.74 kgs)
REGULATIONS		UL, FCC-B, c-UL, CE, TUV/GS, CB Report, PCT
WARRANTY		Three-year limited warranty on parts and labor, first-year Express Exchange® service, one-year warranty on lamp.**
OTHER		Mirror reverse image, upside down image, digital keystone correction

ISO 9001



FM 40187

ISO 14001



EMS 40968

ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.



ViewSonic®
See the difference.®

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789
Phone (800) 888-8583 or (909) 444-8888 • In Canada (866) 262-1967 • Fax (909) 839-7922 • SalesInfo@ViewSonic.com • ViewSonic.com

*Running Whisper-mode exclusively can extend lamp life up to 4,000 hours. **Lamp warranty available in U.S. and Canada. Subject to terms and conditions, verification and approval. Applies to manufacturers installed lamp only. All accessory lamps purchased separately are warranted for 90 days. †Excluding major U.S. holidays. †† Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country. See your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2004 ViewSonic Corporation. All rights reserved. [11756-008-02/04] PJ501-1

For more product information, visit us on the web at ViewSonic.com

specifications