## ViewSonic<sup>®</sup> PJ520 Projector LIGHT, BRIGHT AND PORTABLE



#### Versatile, portable, multimedia projector.

The ViewSonic PJ520 is the perfect union of form and function with 800x600 native resolution. It **WEIGHS IN AT LESS THAN 6 POUNDS** while its **2,000 LUMENS DELIVER ULTRA-BRIGHT, CRISP, CLEAR IMAGES.** Unveil dynamic multimedia presentations in any setting. The multiple video inputs allow connectivity from different sources while one image can be output on an additional dis-

play. Rich in features and light on the wallet, the PJ520 is an excellent choice for business or home use.

ViewSonic<sup>®</sup> has the **best warranty** and **service support** in the business!

**3-Year** Parts and labor limited warranty **1-Year** Free Express Exchange<sup>®</sup>

**1-Year** Limited lamp warranty And we offer free 24/7 technical support<sup>†</sup> for

#### Sharper presentations, brighter images.

#### --->Ideal for mobile professionals

Packs 2,000 lumens in just 5.9 pounds It's the bright choice for the mobile professional.

#### ···· Bright in virtually any setting with 2,000 lumens

#### ---->Ultimate flexibility with multiple RGB inputs

Connect two computers simultaneously or add a video source for dynamic meetings.

#### Supports HD signals including 480i, 480p, 720p, 1080i

Capable of displaying HD signals as well as other video and data sources.\*

#### ··· Whisper-mode extends lamp life

Extend the life of your lamp up to 4,000 hours\*\* and reduce noise output.

#### ···> The perfect image in any setting

Horizontal and vertical digital keystone correction, short focal length, and zoom function ensure the perfect size image in virtually any room.

Technical support wherever, whenever, just in case.

#### ···> The best warranty in the business

Covered by a three-year parts and labor limited warranty, first-year Express Exchange<sup>®</sup> and one-year limited lamp warranty.\*\*\*





Easy-to-use remote included.

# ViewSonic<sup>®</sup> PJ520 Projector

### LIGHT, BRIGHT AND PORTABLE







- 1. Stand by/on 5. Component, composite, and S-video input 2. Menu **3.** Kensington security port **6.** Zoom and focus rings

4. Dual RGB inputs and RGB output

PJ520 Distance Calculator				
Image Size (Diagonal Inches)	Height (Inches)	Width (Inches)	Throw Distance (Inches)	
40	24	32	47 - 57	
60	36	48	71 - 85	
100	60	80	119 - 143	
150	90	120	180 - 216	
200	120	160	240 - 288	
250	150	200	300 - 361	
300	180	240	360 - 433	

Accuracy of the calculations are +/- 5%. For additional calculations visit ViewSonic.com.

#### **Optional Accessories**

- Replacement lamp RLU-150-001 PRJ-HCA-001 Rolling hard case
- Rolling soft case PRJ-SCA-001 Ceiling/Wall Mount PRJ-WMK-005 (not compatible w/ PM-FCP and PRJ-ECM-001)
- Extended Express Exchange<sup>®</sup> EE-LB-02

	Type Pixel Format Lens Zoom Factor	0.7" Poly–Si TFT with micro-lens 800x600 (native resolution) Manual zoom/focus 1.2	
DISPLAY Size Throw Distance Lamp Brightness Contrast Ratio Aspect Ratio		30"-300" 35"-433" 150W, 4,000 hours** 2,000 lumens 350:1 4:3, 16:9	
AUDIO INPUT SIGNAL	Speakers Video Sync Frequency	1x1 watts RGB analog, NTSCM, NTSC 4.45, PAL, SECAM, HDTV (480i, 480p, 720p, 1080i) Separated F <sub>h</sub> :15–91kHz; F <sub>v</sub> :56–120Hz	
COMPATIBILITY	PC Mac <sup>®tt</sup>	Analog: VGA to UXGA (scaled) Analog: up to SXGA (may require Mac adapter)	
CONNECTOR	RGB Input Video Input RGB Output Audio Input USB (Remote control mouse) Control	15-pin HD, D-sub cable (x2) Composite, component, S-video 15-pin HD, D-sub cable (x1) RCA (x1) USB upstream (x1) RS232	
POWER	Voltage Consumption	90–264 VAC, 50–60Hz (universal) 240 watts (typ)	
CONTROLS	Basic OnView <sup>*</sup>	Standby, menu, input, reset, H/V keystone Language, display (keystone, brightness, contrast, aspect, picture position, gamma, mirror, language, color bar (R,B) sharpness, color, tint, H/V position, H. phase, H. size, over scan, auto adjust, video, HDTV, sync on green, blank, start up, myscreen, myscreen size, myscreen lock, whisper, auto off, audio (volume, mute), projection (front, rear, front ceiling, rear ceiling, lamp (lamp timer, lamp timer reset, filter (filter timer, filter timer reset).	
OPERATING CONDITIONS	Temperature Humidity	32–95° F (0–35% C) 10–85% (non-condensing)	
NOISE LEVEL	Normal Whisper mode	39 dB (typ) 34 dB (typ)	
DIMENSIONS (WxHxD)	Physical	295mm x 76mm x 231mm 11.6" x 3.0" x 9.1"	
WEIGHT	Net Gross	5.9 lb. (2.7 kg) 14.5 lb. (6.6 kg)	
REGULATIONS		UL, UL60950 C-UL, FCC B, TUV/GS, CB, CE, C-TICK, TUV-S, NOM	
OTHER		H/V digital keystone correction, soft carrying case, remote with mouse control, dual RGB input, RGB output, auto adjust	
WARRANTY		Three-year limited warranty on parts and labor, first-year Express Exchange® Service. One-year warranty on lamp.***	



#### ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789 Phone (800) 888-8583 or (909) 444-8888 • In Canada (866) 262-1967 • Fax (909) 839-7922 • SalesInfo@ViewSonic.com • ViewSonic.com

\*Optional cables required. \*\*Running whisper-mode exclusively can extend lamp life up to 4,000 hours. \*\*\*Three-year limited warranty and 1-year limited map warranty available in U.S. and Canada for current projector models purchased on or after May 1, 2002. Applies to manufacturer's installed lamp only. All accessory lamps purchased separately are warranted for 90 days. Subject to terms and conditions, verification and approval. For Express Exchange program details, visit ViewSonic.com. (Excludes U.S. holidays, †) Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs vary by country. See your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2004 ViewSonic Corporation. All rights reserved. [11737-008-02/04] PJ-520-1

For more product information, visit us on the web at ViewSonic.com