ViewSonic® PJ550 Projector

ULTRA-PORTABLE XGA PROJECTOR



High-performance at an exceptional value.

The PJ550 is the ideal ultra-light portable projector for anyone putting in time on the road. At a bright 1,200 lumens, this XGA projector delivers sharp images and rich color. True 1024x768 resolution (1280x1024 maximum) produces exceptional image quality for both data and video. The PJ550's short focal length and zoom offer versatility in any setting, and digital keystone

correction assures
professional presentations.
Whisper-mode setting
prolongs lamp life and
makes the PJ550 an
excellent investment value —
ideal for the mobile
presenter.

ViewSonic has the best warranty and service support in the business!

3-Year Parts and labor limited warranty

1-Year Free Express Exchange®

1-Year Lamp warranty

High brightness and versatility.

··· Ideal for mobile professionals.

The PJ550 packs 1,200 lumens in just 5.3 lbs. It's the bright choice for the mobile professional who demands brilliant images in virtually any setting.

··· Crisp, clear, flexible presentations.

Offering HD capability, native XGA resolution (1024x768), and standard (4:3) and wide-screen (16:9) aspect ratios your images are crisp and clear, your presentation options unlimited.



Easy-to-use remote included.

****Whisper-mode extends lamp life and reduces noise output.

Use the whisper-mode function to reduce noise output and extend the life of your lamp up to 4,000 hours*.

··· The perfect image in any setting.

Set up quickly, anywhere. Digital keystone correction, short focal length, and zoom function ensure the perfect size image in any meeting environment.

··· Technical Support wherever, whenever you need it.

Free industry-leading 24/7 customer support,† just in case.

··· The best warranty in the business.

Feel secure knowing you're, covered by a three-year parts and labor limited warranty, first-year Express Exchange® and one-year lamp warranty.**





ViewSonic® PJ550 Projector

ULTRA-PORTABLE XGA PROJECTOR





- 1. Power button
- 2. Input select
- 3. Keystone correction
- 4. Reset
- 5. Menu
- 6. Component, composite, S-video input
- 7. RGB input
- 8. Zoom and focus rings
- 9. Front foot adjuster

	PJ550 Distance Calculator					
Image Size (Diagonal in.)		Height (in.)	Width (in.)	Throw Distance (in.)		
	40	24	32	47		
	60	36	48	71		
	80	48	64	95		
	100	60	80	119		
	150	90	120	180		
	200	120	160	240		
	250	150	200	300		
	300	180	240	360		

Accuracy of the calculations are +/- 5%. For additional calculations visit Viewsonic.com.

Optional	Access	ories
~ .		

(RLC-150-003) Replacement lamp

(PRJ-HCA-001)

· Ceiling/wall mount kit (PRJ-WMK-001)

ULTRA-PORTABLE XGA PROJECTOR

OLI KA-POKIA	IDLE AUA FR	OJECION
LCD	Туре	3-panel 0.7" TFT active matrix LCD
	Resolution	XGA 1024x768 compressed to 1280x1024
	Pixel Format	1024 Horizontal x 768 Vertical
	Lens	Manual zoom (manual x 1.2)/focus
		· "
DISPLAY	Size	30"–300" (measured diagonally)
	Throw Distance	0.7m-9.0m (2.3'-29.5')
	Lamp	150W UHB Compact, 4,000* hour rating
	Brightness	1,200 lumens
	Contrast Ratio	300:1
	Keystone Correction	±10 degrees
	Aspect Ratio	4:3, 16:9
		·
AUDIO	Speaker	1W monospeaker
INPUT SIGNAL	Computer	RGB analog
	Video	NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, PAL 60, SECAM, 480i, 480p, 720p,
		1080i
	Sync	Separated and composite
	Frequency	Fh: 15~78kHz; Fv: 56~120Hz
		<u> </u>
COMPATIBILITY		From VGA up to SXGA
	Mac®#	Up to SXGA (may require Mac Adapter)
CONNECTOR	RGB Input	15-pin HD, D-sub (x1)
	Composite Video	• • • • • • • • • • • • • • • • • • • •
	S-Video	Mini-Din 4 pin (x1)
	Component	RCA (x3)
	Audio In	RCA (x1)
	Control	
	Control	RS232
POWER	Voltage	100–120V AC / 220–240V AC
	Consumption	210W (typ), 130W (whisper-mode)
USER CONTROLS	Rasic	Standby on/off, menu (left, right, up, down), input, reset, mute, indicator
OSER COMMOES	Dusic	(lamp, power, temp)
	Remote	
	Kelliote	Standby on/off, video, RGB, menu, position, menu select (left, right, up,
		down), reset, freeze, magnify (+, -, off), volume (up, down), mute, keystone,
	0	auto, blank
	OnView [®]	Brightness, contrast, V. position, H. position, H. phase, H. size, color balance
		(red), color balance (blue), aspect ratio, auto, RGB, blank, mirror, start up,
		volume, menu color, timer, language, auto off, sync on green
OPERATING	Temperature	32° F–95° F (0° C–35° C)
CONDITIONS	Humidity	10%–85% (non-condensing)
		<u> </u>
DIMENSIONS	Physical	289mm (W) x 210mm (D) x 84mm (H)
		(11.3" x 8.26" x 3.3")
WEIGHT	Net	2.4 kg. (5.3 lb)
	Gross	6.3 kg. (13.9 lb)
DECILIATIONS		
REGULATIONS		UL, FCC-B, c-UL
WARRANTY		Three-year limited warranty on parts and labor, first year Express
		Exchange® service, one-year warranty on lamp.**
OTHER		Mirror reverse image, upside down image, digital keystone correction
V.IIEN		mintor reverse image, apside down image, digital resitorie correction



· Rolling soft case (PRJ-SCA-001)

 Extended Express Exchange[®] Service (EE-LB-02)



ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789 Phone (800) 888-8583 or (909) 444-8888 • In Canada (866) 262-1967 • Fax (909) 839-7922 • SalesInfo@ViewSonic.com • ViewSonic.com

^{*} Running Whisper-mode exclusively can extend lamp life up tp 4,000 hours. **Third-year limited warranty and 1-year limited lamp warranty apply only to P1550 projectors purchased on or after May 1, 2002. Lamp warranty subject to terms and conditions, verification and approval. Applies to manufacturer's installed lamp only. All accessory lamps purchased separately are warranted for 90 days. For Express Exchange program details, visit ViewSonic.com. †Excluding major U.S. holidays. ††Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country, see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2004 ViewSonic Corporation. All rights reserved. [11757-00B-02/04] PI550-1