

ViewSonic® PJ551 Projector

Ultra-Portable XGA Projector



See the difference.®



Step up to the PJ551 for higher brightness.

The ViewSonic PJ551 projector offers high performance in an ultra-light 5.4 pound package. Displaying 1,500 lumens and a high contrast ratio, the PJ551 delivers vibrant, rich colors with life-like depth, even in well-lit rooms. True 1024x768 resolution (1280x1024 maximum) produces exceptional image quality for both data and video. Short focal length and zoom let you set up just about anywhere. For performance and value, choose the projector that shines, the ViewSonic PJ551.

High brightness and versatility.

❖ Ideal for mobile professionals.

The PJ551 packs 1,500 lumens in just 5.4 lbs. It's the bright choice for the mobile professional who demands brilliant images in virtually any setting.

❖ Crisp, clear, flexible presentations.

Offering HD capability, scalable to SXGA resolution, and standard (4:3) and wide-screen (16:9) aspect ratios your images are crisp and clear, your presentation options unlimited.

❖ Whisper-mode extends lamp life and reduces noise output.

Use the whisper-mode function to reduce noise output and extend the life of your lamp up to 4,000 hours*.

❖ The perfect image in any setting.

Set up quickly, anywhere. Digital keystone correction, short focal length, and zoom function ensure the perfect size image in any meeting environment.

❖ Technical Support wherever, whenever you need it.

Free industry-leading 24/7 customer support,† just in case.

❖ The best warranty in the business.

Feel secure knowing you're, covered by a three-year parts and labor limited warranty, first-year Express Exchange® and one-year lamp warranty.**

ViewSonic has the **best new warranty** and **service support** in the business!



3-Year parts and labor limited warranty

1-Year Free Express Exchange®

1-Year Lamp warranty

And we offer free 24/7† technical support for the life of your product, just in case.

Super bright



ViewSonic®
See the difference.®

ViewSonic® PJ551 Projector

Ultra-Portable XGA Projector



PJ551 Distance Calculator

Image Size (Diagonal in inches)	Height (in inches)	Width (in inches)	Throw Distance (in inches)
24	14.42	19.12	21.52
48	28.85	38.24	45.04
72	43.28	57.36	68.56
96	57.71	76.48	92.08
120	72.14	95.6	115.6
144	86.57	114.73	139.12
168	101	133.84	162.63
192	115.43	152.97	186.16

Accuracy of the calculations are +/- 5%.
For additional calculations visit ViewSonic.com.

Optional Accessories

Replacement lamp	RLC-150-003
Wall/ceiling mount	PRJ-WMK-001
Rolling hard case	PRJ-HCA-001
Rolling soft case	PRJ-SCA-001
Extended Express Exchange*	EE-LB-02

ULTRA-PORTABLE XGA PROJECTOR

LCD	Type	3-panel 0.7" TFT active matrix LCD
	Resolution	XGA 1024x768 compressed to 1280x1024
	Pixel Format	1024 horizontal x 768 vertical
	Lens	Manual zoom/focus (manual x 1.2)
DISPLAY	Size	30"-300" (measured diagonally)
	Throw Distance	2.3'-29.5' (.7m-9m)
	Lamp	150W UHB Compact, 4,000* hour rating
	Brightness	1,500 lumens
	Contrast Ratio	400:1
	Keystone Correction	±10 degrees
ASPECT RATIO	Aspect Ratio	4:3, 16:9
	AUDIO	Speaker 1W monospeaker
INPUT SIGNAL	Computer Video	RGB analog NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, PAL 60, SECAM, 480i, 480p, 720p, 1080i
	Sync Frequency	Separated and composite Fh: 15~78kHz; Fv: 56~120Hz
COMPATIBILITY	PC Mac**††	From VGA up to SXGA Up to SXGA (may require Mac adapter)
CONNECTOR	RGB Input	15-pin HD, D-sub (x1)
	Composite Video	RCA (x1)
	S-Video	Mini-Din 4 pin (x1)
	Component	RCA (x3)
	Audio In Control	RCA (x1) RS232
POWER	Voltage Consumption	100-120V AC / 220-240V AC, 50-60Hz (universal) 210W (typ), 130W (whisper-mode)
USER CONTROLS	Basic	Standby on/off, menu (left, right, up, down), input, reset, mute, indicator (lamp, power, temp)
	Remote	Standby on/off, video, RGB, menu, position, menu select (left, right, up, down), reset, freeze, magnify (+, -, off), volume (up, down), mute, timer, auto, blank
	OnView®	Brightness, contrast, V. position, H. position, H. phase, H. size, color balance (red), color balance (blue), aspect ratio, auto, RGB, keystone, blank, mirror, start up, volume, menu color, timer, language, auto off, sync on green
OPERATING CONDITIONS	Temperature	32-95° F (0-35° C)
	Humidity	10-85% (non-condensing)
NOISE LEVEL	Normal	42 dB (typ)
	Whisper	37 dB (typ)
DIMENSIONS	Physical	11.3" x 8.26" x 3.3" 289mm x 210mm x 84mm
	WEIGHT	Net
Gross		13.9 lbs. (6.3 kgs)
REGULATIONS		UL, FCC-B, c-UL, CE, TUV/GS, CB Report, PCT
WARRANTY		Three-year limited warranty on parts and labor, first-year Express Exchange* service, one-year warranty on lamp.**
OTHER		Soft carry case, mirror reverse image, upside down image, digital keystone correction



FM 40187



EMS 40968

ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.



ViewSonic®
See the difference.®

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789
Phone (800) 888-8583 or (909) 444-8888 • In Canada (866) 262-1967 • Fax (909) 839-7922 • SalesInfo@ViewSonic.com • ViewSonic.com

*Running Whisper-mode exclusively can extend lamp life up to 4,000 hours. **Lamp warranty available in U.S. and Canada. Subject to terms and conditions, verification and approval. Applies to manufacturers installed lamp only. All accessory lamps purchased separately are warranted for 90 days. †Excluding major U.S. holidays. †† Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country. See your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2004 ViewSonic Corporation. All rights reserved. [11758-008-02/04] PJ551-1

For more product information, visit us on the web at ViewSonic.com

Specifications