PJ552

LIGHT, BRIGHT AND PORTABLE PROJECTOR

WITH KEYSTONE CORRECTION

Performance and reliability.

The ViewSonic[®] PJ552 offers bright images for office presentations and impressive home entertainment viewing with 1,500 lumens and 1024x768 XGA native resolution. This small, powerful projector steps up to deliver high-resolution images and sharp text, spreadsheets and graphics. An optical zoom lens, short focal length and digital keystone correction project precise images in virtually any setting. Advanced features like video PROGRESSIVE SCAN AND 3:2 PULL DOWN DELIVER SMOOTHER VIDEO PERFORMANCE FOR HOME THEATER ENTERTAINMENT. Multiple inputs allow you to connect two PCs or add a video source for DYNAMIC MULTIMEDIA PRESENTATIONS.

A BRIGHT, AFFORDABLE CHOICE FOR HOME AND OFFICE

> Bright in any setting with 1,500 lumens

Packs 1,500 lumens in just 5.6 lbs. It's the bright choice for mobile presenters.

> Ultimate video source flexibility

Connect two computers simultaneously or add a video source for dynamic meetings. Add another monitor output to view the same projected image on another display.

> Supports HD signals including 720p and 1080i*

> Advanced video features

Progressive scan and 3:2 pull down for superior video performance.

> Whisper-mode extends lamp life

Extend the life of your lamp up to 4,000 hours** and reduce noise output.

> The perfect image in any setting

Set up quickly, anywhere. Digital keystone correction, auto tune and optical zoom function ensure the perfect image in any room.

The best warranty in the business

Covered by a three-year parts and labor limited warranty, first-year Express Exchange® and one-year limited lamp warranty.***



VIEWSONIC PRODUCTS, PROGRAMS, AND SERVICES



the choice of professionals

PJ552 LIGHT, BRIGHT AND PORTABLE PROJECTOR WITH KEYSTONE CORRECTION







and laptop bagPRJ-SCA-004
• Ceiling mountPRJ-WMK-013
• Universal ceiling mount kitWMK-005

Optional Accessories

• Soft case with wheels

PROJECTOR	Туре	0.7" Poly-Si TFT with micro-lens, TFT active matrix
	Pixel Format	1024x768 XGA
	Lens	Manual zoom, manual focus
	Zoom Factor	1.2
	Keystone	Vertical \pm 15°
DISPLAY	Size	30"–300" (diagonally)
	Throw Distance	35"-443"
	Throw Ratio	1.5~1.8:1
	Lamp	165W, 2,000 hours**
	Brightness	1,500 ANSI lumens
	Contrast Ratio	400:1
	Aspect Ratio	4:3 (native), 16:9
AUDIO	Speakers	1x1 watt
INPUT SIGNAL	Computer and Video	RGB analog, NTSC M, NTSC 4.45, PAL, SECAM, HDTV (480i, 480p, 576i, 720p, 1080i)
	Frequency	F _h : 15–91kHz; F _v : 50–120Hz
COMPATIBILITY	PC	Analog: from VGA up to UXGA (scaled)
	Mac®†	Analog: up to SXGA (may require a Mac adapter)
CONNECTOR	RGB (input)	DB-15 (x2)
	RGB (output)	DB-15 (x1)
	Composite Video (input)	RCA jack (x1)
	S-Video (input)	Mini-Din 4-pin (x1)
	Component Video (input)	RCA jack (x1 set)
	Audio (input)	Stereo mini-jack (x2)
	Audio (output)	Stereo mini jack (x1)
	USB	USB (x1) for mouse control
	Control	9-pin D-sub for RS232 control
POWER	Voltage	100–240 VAC, 50/60Hz (universal)
	Consumption	240W (typ)
CONTROLS	Basic	Standby/On, menu, input, reset, H/V keystone
	OnView®	Language, Display (brightness, contrast, gamma, color tem-
		perature, color, tint, sharpness), progressive, My Memory,
		aspect, overscan, V. position, H. position, H. Phase, H. size
		auto adjust, color space, component, video format, frame lock
		S-aspect, information, V. keystone, whisper, mirror, volume,
		language, menu position, OSD bright, blank color, start up
		My Screen, My Screen Lock, message, auto search, auto
		power off, auto power on, lamp time, filter time, service menu
OPERATING	Temperature	32-95°F (0-35°C)
CONDITIONS	Humidity	10–85% (non-condensing)
NOISE LEVEL	Normal	38 dB (typ)
	Whisper Mode	32 dB (typ)
DIMENSIONS	Physical (mm)	297mm x 65mm x 233mm
W x H x D)	Physical (in.)	11.7" × 2.6" × 9.2"
WEIGHT	Net	5.6 lb. (2.5 kg)
	Gross	13.9 lb. (6.3 kg)
REGULATIONS		UL 60950, C-UL, FCC-B, ULDEMKO, TUV-S, CB, CE, C-TICK, NOM
OTHER		Digital keystone correction, auto adjust, 3:2 pull down,
		progressive scan, frame lock, overscan
PACKAGE CONTENTS		Projector, power cords, VGA cable, RCA video cable,
		remote control, soft case, lens cap, ViewSonic Wizard CD,
		Quick Start Guide
WARRANTY		Three-year limited warranty on parts and labor, first-year
		Express Exchange® Service. One-year limited warranty on



the choice of professionals

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

Customer Service and Technical Support: (800) 688-6688 • Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

*Optional cables required. **Running whisper-mode exclusively can extend lamp life. ***Visit ViewSonic.com for full details. †Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs vary by country. See your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2006 ViewSonic Corporation. All rights reserved. [12747-008-01/06] PJ552-1

For more product information, visit us on the web at ViewSonic.com