

ViewSonic® PJ750 Projector

High Brightness. Ultra-Portable.



Bright, versatile and portable.

The ViewSonic PJ750 projector delivers exceptionally bright presentations. With 2,300 lumens, 1024x768 XGA resolution and high contrast, this projector delivers clear, crisp images, even in well-lit rooms. Easy to use, the **FULL-FEATURED** PJ750 offers zoom and digital keystone correction as well as **MULTIPLE COMPUTER AND VIDEO INPUTS AND OUTPUTS FOR GREATER FLEXIBILITY**. Whisper-mode will make the most out of your investment by extending the lamp life and reducing noise output to whisper quiet levels. With the PJ750 projector, you'll confidently present a positive image anytime, anywhere.

High brightness and versatility.

❖ Ideal for mobile professionals.

Packs 2,300 lumens in just 7.2 lbs. It's the bright choice for the mobile professional.

❖ Supports HD signals including 480i, 480p, 720p, 1080i

Capable of displaying HD signals as well as other video and data sources.

❖ Ultimate flexibility with multiple RGB inputs.

Connect two computers simultaneously or add a video source for dynamic meetings.

❖ Easy set-up and auto tuning.

One-touch setup button for fast, easy sync and sharp focus.

❖ The perfect image in any setting.

Digital horizontal and vertical keystone correction, short focal length and zoom function ensure the perfect size image in any room.

❖ Whisper-mode extends lamp life.

Extend the life of your lamp up to 4,000 hours* and reduce noise output.

❖ Free industry-leading 24/7 customer support.†

Technical Support wherever, whenever, just in case.

❖ The best warranty in the business.

Covered by a three-year parts and labor limited warranty, first-year Express Exchange® and one-year lamp warranty. **

ViewSonic has the **best warranty** and **service support** in the business!



3-Year Parts and labor limited warranty

1-Year Free Express Exchange®

1-Year Limited lamp warranty**

And we offer free 24/7† technical support for the life of your Product, just in case.

Super bright



ViewSonic®
See the difference.®

ViewSonic® PJ750 Projector

High Brightness. Ultra-Portable.



PJ750 Distance Calculator

Image Size (Diagonal in inches)	Height (in inches)	Width (in inches)	Throw Distance (in inches)
24	14.45	19.19	42.73
48	28.91	38.38	81.47
72	43.37	57.58	120.2
96	57.83	76.77	158.94
120	72.29	95.97	197.68
144	86.75	115.16	236.41
168	101.21	134.36	275.15
192	115.67	153.55	313.88

Accuracy of the calculations are +/- 5%.
For additional calculations visit ViewSonic.com.

Optional Accessories

Rolling hard case	PRJ-HCA-001
Rolling soft case	PRJ-SCA-001
Spare lamp	PRJ-RLC-001
Ceiling/wall mount kit	PM-750
Extended Express Exchange® service	EE-LB-02

PORTABLE HIGH-BRIGHTNESS PROJECTOR

LCD	Type	0.9" Polysilicon (x3) stripe pixel TFT active matrix
	Pixel Format	1024 horizontal x 768 vertical
	Lens	Manual zoom/focus (1:1.3x)
DISPLAY	Size	30"-300" (measured diagonally)
	Throw Distance	3.9'-51.0' (1.2m-15.7m)
	Lamp	200W UHB compact, 4,000 hour rating*
	Brightness	2,300 lumens
	Contrast Ratio	400:1
AUDIO	Speakers	Stereo
	Power	1Wx2
INPUT SIGNAL	Computer Video	RGB analog
	Video	NTSC, PAL-M, PAL-N, SECAM, 480i, 480p, 720p, 1080i
	Sync	Separated and composite
	Frequency	Fh: 15~91kHz; Fv: 56~120Hz
COMPATIBILITY	PC	From VGA up to SXGA
	Mac®††	Up to SXGA (may require Mac®†† Adapter)
CONNECTOR	RGB Input	15-pin HD, D-sub (x2)
	RGB Output	15-pin HD, D-sub (x1)
	Composite Video	RCA (x1)
	Component Video	RCA (x3)
	S-Video	Mini-Din 4 pin (x1)
	Audio (In/Out)	In RCA (L/Rx1) and 3.5mm (x2); Out 3.5mm (x1)
	Control	RS232
	USB	USB upstream (x1), mouse control
POWER	Voltage	100-220V AC/120-240V AC
	Frequency	50-60Hz (universal)
	Consumption	290W (typ)
USER CONTROLS	Basic	Standby on/off, menu (left, right, up, down), input, reset, mute, keystone, indicator (lamp, power, temp)
	Remote	Standby on/off, video, laser, blank, RGB, disk pad, auto, mouse, menu, position, menu select (left, right, up, down), reset, freeze, magnify (+, -, off), volume (up, down), mute, timer
	OnView®	Brightness, contrast, V. position, H. position, H. phase, H. size, color balance (red), color balance (blue), aspect ratio, auto, RGB, keystone, blank, mirror, start up, volume, menu color, timer, language, auto off, sync on green
OPERATING CONDITIONS	Temperature	32° F-95° F (0° C-35° C)
	Humidity	10%-85% (non-condensing)
NOISE LEVEL	Normal	41 dB (typ)
	Whisper	35 dB (typ)
DIMENSIONS (W X H X D)	Physical	11.7" x 3.0" x 9.0" 298mm x 76mm x 228mm
	Net	7.2 lbs. (3.25 kgs)
WEIGHT	Gross	16.5 lbs. (7.5 kgs)
	REGULATIONS	UL, FCC-B, c-UL, CE, CB Report, TUV/GS, CB Report, VCCI, BSMI, PCT
OTHER	Soft carry case, mirror reverse image, horizontal/vertical keystone correction, remote with mouse and laser pointer	
WARRANTY	Three-year limited warranty on parts and labor, first-year Express Exchange® service, one-year warranty on lamp.	

ISO 9001



FM 40187

ISO 14001



EMS 40968

ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.



ViewSonic®
See the difference.™

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789
Phone (800) 888-8583 or (909) 444-8888 • In Canada (866) 262-1967 • Fax (909) 839-7922 • SalesInfo@ViewSonic.com • ViewSonic.com

*Running Whisper-mode exclusively can extend lamp life up to 4,000 hours. **Lamp warranty available in U.S. and Canada. Subject to terms and conditions, verification and approval. Third-year and 1-year limited lamp warranties apply only to PJ250, PJ350, PJ500, PJ501, PJ510, PJ550, PJ551, PJ650, PJ750, and PJ1065 projectors purchased after May 1, 2002. Applies to manufacturers installed lamp only. All accessory lamps purchased separately are warranted for 90 days. †Excluding major U.S. holidays. †† Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country. See your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2004 ViewSonic Corporation. All rights reserved [11760-008-02/04] PJ750-3

For more product information, visit us on the web at ViewSonic.com

Specifications