

Brilliant multimedia presentations

ViewSonic's PJ766D is the class-leading multimedia DLP™ projector that delivers brilliant color, sharp graphics and outstanding video. The DIGITAL CLARITY OF DLP TECHNOLOGY GUARANTEES STUNNING LIFELIKE video and crisp data presentations. The native 1024x768 XGA resolution and an extremely high 2,500 lumens of brightness make it ideal for installations in conference rooms, religious sanctuaries, lecture halls and home theaters. The PJ766D offers multiple inputs including RGB, DVI-I, component, composite and S-video that ALLOW YOU TO CUSTOMIZE MULTIMEDIA PRESENTATIONS. Impress your audience with the power and performance of the PJ766D.

PJ766D

HIGH BRIGHTNESS DLP™ MULTIMEDIA PROJECTOR

WITH DIGITAL (DVI) CONNECTIVITY



POWER AND PERFORMANCE.

- > **Bright in virtually any setting with 2,500 lumens**
Packs 2,500 lumens in just 7.9 lbs. It's the bright choice for mobile presenters.
- > **Supports HD signals including 720p and 1080i**
Capable of displaying HD signals as well as other video and data sources*.
- > **Easy set up and auto tuning**
Auto source detection and auto sync.
- > **The perfect image in any setting**
Digital keystone correction, short focal length and zoom function ensure the perfect size image in any room.
- > **Whisper-mode extends lamp life**
Extend the life of your lamp up to 4,000 hours** and reduce noise output.
- > **Ultimate flexibility with multiple inputs**
Rich connectivity with RGB, DVI, component video, composite video and S-video inputs and a monitor output.
- > **The best warranty in the business**
Covered by a three-year parts and labor limited warranty, first-year Express Exchange® and one-year limited lamp warranty.**



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

ViewSonic 
the choice of professionals

PJ766D

HIGH BRIGHTNESS DLP™ MULTIMEDIA PROJECTOR WITH DVI



Optional Accessories

- ATA hard shipping caseCASE-003
- Rolling soft case and laptop bagPRJ-SCA-004
- Replacement lampRLC-016
- Universal ceiling mount kitWMK-005
- Extended Express Exchange®PRJ-EE-08-03

PROJECTOR	Type	0.7" XGA Digital Micromirror Device (DLP™)
	Pixel Format	1024x768 XGA (native resolution)
	Lens	Manual zoom/ manual focus
	Zoom Factor	1.2
	Keystone	Vertical ± 15°
DISPLAY	Size	37.5"–240" (diagonally)
	Throw Distance	58.8"–314.4"
	Throw Ratio	1.6–2:1
	Lamp	200W, 3,000 hours**
	Brightness	2,500 ANSI lumens
	Contrast Ratio	2000:1
INPUT SIGNAL	Aspect Ratio	4:3 (native), 16:9
	Video	NTSC 4.43, PAL, SECAM, HDTV (480i, 480p, 576i, 720p, 1080i)
COMPATIBILITY	Frequency	F _H : 31–90kHz; F _V : 50–85Hz
	PC	Analog: from VGA up to SXGA (scaled)
CONNECTOR	Mac®†	Analog: up to SXGA (may require a Mac adapter)
	RGB (input)	DB-15 (x1)
	DVI (input)	DVI-I (x1)
	RGB (output)	DB-15 (x1)
	Composite Video (input)	RCA jack (x1)
	S-Video (input)	Mini-DIN 4-pin (x1)
	Component Video (input)	RCA jack (x3)
	Control	RS-232 (mini-din, 3-pin)
	Audio (input)	Mini-Jack (x1); RCA (x1)
	Audio (output)	Mini-Jack (x1)
	POWER	Voltage
Consumption		255W (typ)
CONTROLS	Basic	Standby, menu, input, reset, H/V keystone
	OnView®	Main menu (brightness, contrast, sharpness, color temp, color saturation, color, tint, gamma, color space, reset), setup menu (H. position, V. position, keystone, aspect ratio, advance feature, reset), advanced feature menu (user color, white peaking, logo display, reset), configuration menu, utility menu, language menu, status menu
OPERATING CONDITIONS	Temperature	41–95°F (5–35°C)
	Humidity	5–95% (no condensing)
NOISE LEVEL	Normal	35 dB (typ)
	Whisper Mode	33 dB (typ)
DIMENSIONS (W x H x D)	Physical (mm)	328mm x 88mm x 238mm
	Physical (in.)	12.9" x 3.5" x 9.4"
WEIGHT	Net	7.9 lb. (3.6 kg)
	Gross	14.3 lb. (6.5 kg)
REGULATIONS	UL/C-UL, FCC-B, TUV, CB, CCC, NOM	
CONTENTS	Projector, power cord, VGA cable, remote control, lens cap, ViewSonic Wizard CD, Quick Start Guide, S-video cable, DVI to HD-15 cable, soft carry case, ViewSonic Wizard CD, Quick Start Guide	
WARRANTY	Three-year limited warranty on parts and labor, first-year Express Exchange® Service. One-year limited warranty on lamp***	

ViewSonic® 

the choice of professionals

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

Customer Service and Technical Support: (800) 688-6688 • Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

*Optional cables required. **Running whisper-mode exclusively can extend lamp life. ***Visit ViewSonic.com for details. †Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs vary by country. See your ViewSonic representative for complete details. DLP™ is a trademark of Texas Instruments. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2006 ViewSonic Corporation. All rights reserved. [12708-00B-11/05] PJ766D-1

For more product information, visit us on the web at ViewSonic.com