

# ViewSonic® PJ853 Projector

## LiteBird™ Series



### LiteBird Micro Portable Projector

At only 5.3 pounds and 3" tall, the LiteBird PJ853 is ideal for mobile presenters. This micro-portable ultra-slim projector fits easily into an attache case with a notebook computer, and its superior three-panel LCD system gives sharp, crisp images. The 800 lumens and 300:1 contrast ratio of the PJ853 make images easy to view even in well-lit rooms. It also supports many applications, ensuring computer compatibility and maximum image fidelity. Digital keystone correction provides a square image when projecting from most any angle and the short focal length makes it very versatile. Presentations are worry free with an auto-setup command that allows for quick and easy starts. ViewSonic's PJ853 is the right choice for any mobile presenter.

- **True SVGA 800 x 600 resolution**  
Displays clear, crisp images in true SVGA or compressed XGA 1024 x 768 resolution.
- **800 lumens of brightness**  
Compatible with most major notebook computers while supporting a wide variety of applications.
- **Micro portable, ultra-slim design**  
Weighs only 5.3 pounds with the footprint of a notebook computer and a height of 3".
- **Industry leading 24/7 customer support**
- **Increased flexibility with short focal length**



**ViewSonic®**  
*See the difference.®*

# ViewSonic®

## PJ853 Projector



### MIRCO PORTABLE PROJECTOR

TECHNOLOGY	<b>Type</b>	3 panel 0.7" LCD, TFT active matrix
	<b>Resolution</b>	SVGA 800 x 600
	<b>Pixel Format</b>	800 Horizontal x 600 Vertical
	<b>Lens</b>	Manual focus, manual zoom (1:1.3x) F 2.0-2.5, (f = 17.7 - 21.2mm)
DISPLAY	<b>Colors</b>	16.7 million
	<b>Size</b>	30"-300" (787mm - 7620mm)
	<b>Proj. Distance</b>	2'-30' (0.7m - 9.0m)
	<b>Lamp</b>	130W UHB Compact
	<b>Brightness</b>	800 lumens
AUDIO	<b>Speakers</b>	Mono
	<b>Power</b>	1W
INPUT SIGNAL	<b>Video</b>	RGB analog, NTSC, PAL, SECAM, S-Video
	<b>Sync</b>	H/V Separated (TTL)
	<b>Frequency</b>	Fh;15.75/15.63Khz, 25-78Khz, Fv: 56-120Hz
COMPATIBILITY	<b>PC</b>	PC and compatibles (from VGA up to 1024 x 768 non-interlaced)
	<b>Mac®</b>	Power Mac™ (up to 1024 x 768)
CONNECTOR	<b>RGB Input</b>	15-pin HD Mini D-sub
	<b>Video</b>	RCA x1 (composite) S-Video S-Connector (separate)
	<b>Audio In</b>	M3 stereo mini jack
	<b>Power</b>	3 pin plug (CEE22)
POWER	<b>Voltage</b>	AC 100-240VAC, 50-60 auto
	<b>Consumption</b>	200W
USER CONTROLS	<b>Physical</b>	Standby on/off, menu (left, right, up, down), input, reset, mute
	<b>Remote</b>	Power, menu, volume +/-, mute, laser, freeze, magnify +/- off, left, right, up down, blank, timer, input, position on, cursor, reset
	<b>OSD-RGB Input</b>	Brightness, volume, contrast, color H/V position, H phase, H size, input select, mirror, blank, reveal, message, com speed/bits, timer, 7 language, auto off, start up
	<b>OSD-Video Input</b>	Brightness, volume contrast, sharpness, tint, mirror, H/V position, H phase, H size, color balance, blank, input select, video direct, reveal, message, timer, com speed/bits, 7 language, auto off, start up
OPERATING CONDITION	<b>Temperature</b>	32°F to 95°F (0°C to 35°C)
	<b>Humidity</b>	10% – 85% (no-condensation)
DIMENSIONS	<b>Physical</b>	285mm (W) x 71mm (H) x 203mm (D) 11.3" (W) x 3.0" (H) x 8.3" (D)
	<b>Net</b>	2.35 kg (5.3 lbs.)
REGULATIONS		UL, FCC-B, CSA, CE, CB, PCT, TUV
OTHER		DDC1, DDC2B
ACCESSORIES		Power cord (x3), VGA cable, RCA video/audio cable, s-video cable, stereo mini jack, wireless remote control, battery, soft carrying case

- **Digital keystone correction**

Squares the picture even when projecting at an angle.

- **Three panel LCD optical engine**

Three 0.7" polysilicon LCD panels deliver superb picture quality for sharp, well saturated color images.

- **AutoTune™**

One-touch setup button for fast, easy sync and sharp focus.

- **User replaceable 130w UHB extended life lamp**

Extended lamp life up to 2,000 hours.

- **Wireless remote control**

This offers the presenter total control, flexibility and convenience.

- **Optional accessories**

Executive carrying case	EC1
Replacement lamp	RLC-130-03A
Ceiling/wall mount kit	PM-853
Extended warranty	EXT WTY-LB
48 hour Express Exchange®	EE-LB

ISO 9001



FM 40187

ISO 14001



EMS 40968

ViewSonic Corporation's QMS/EMS has been registered to ISO 9001 & ISO 14001 by the British Standards Institution.



**ViewSonic®**  
See the difference.®

381 Brea Canyon Road, Walnut, CA 91789 Toll Free (866) LITEBIRD (866)548-3247 or (909) 839-7925 • Fax (909) 444-5636 • ViewSonic.com