

ViewSonic®

PJ875 Projector

LiteBird™ Series



- **Light weight and ultra compact**
5 pound micro portable with a vertical slim profile for easy travel.
- **Professional-level 1000 ANSI Lumens**
Projects bright images in well-lit rooms.
- **True SVGA 800 x 600 resolution, compressed XGA 1024 x 768**
Compatible with most major notebook computers while supporting a wide variety of applications.
- **Digital keystone correction**
Squares the picture even when projecting at an angle.
- **Texas Instruments DLP™ digital light processing**
Superb picture quality and color uniformity.
- **Picture-in-Picture capability**
View video and computer data simultaneously for added utility and excitement.
- **PersonalTheater™ projection for movies, sports and more**
Connect DVD, VCR and TV signals for full motion video at work or home.
- **Built in zoom & focus lens for extra flexibility and functionality**

FEATURE-RICH, ULTRA-BRIGHT AND LIGHTWEIGHT

ViewSonic's LiteBird PJ875 is a full-featured, micro-portable projector that delivers every time. You'll walk into any business setting with confidence knowing the PJ875 offers superb image quality high brightness and reliability making your presentations look their best even in well-lit rooms. The LiteBird PJ875 projects at 1000 lumens, accepts SVGA to XGA resolutions and has a 450:1 contrast ratio. Adjustable zoom, digital keystone correction, video picture-in-picture, long lamp life, remote control and a soft carry case make this projector an excellent choice in any presentation setting. This projector also delivers great video and can turn any wall in your home into a big-screen home entertainment system. Choose the LiteBird PJ875 when your presentations count most.



www.ViewSonic-projectors.com

ViewSonic® PJ875 Projector



- Wireless remote control**
 This offers the presenter total control, flexibility and convenience.
- Auto Tuning**
 One-touch setup button for fast, easy sync and sharp focus.
- Industry leading 24/7 technical and customer support**
- Ceiling & Wall mount options available**
- Soft carry case included for easy travel**
 Optional rugged hard case also available
- Optional accessories**

Executive carrying case	EC1
Replacement lamp	RLC-150-07A
Ceiling/wall mount kit	PM-875
Extended warranty	Various
48 hour Express Exchange®	Various

Projection Distance	Image Size Range
1.0m	0.4m – 0.6m
2.0m	0.9m – 1.1m
3.0m	1.3m – 1.7m
4.0m	1.7m – 2.2m
5.0m	2.1m – 2.8m
6.0m	2.6m – 3.3m
7.0m	3.1m – 3.9m
8.0m	3.4m – 4.4m
9.0m	3.8m – 5.0m
10.0m	4.2m – 5.5m

COLOR DMD SVGA MICRO PORTABLE PROJECTOR DISPLAY

DLP	Type Aspect Ratio Lens	T1 0.7" SVGA, Digital Micromirror Device (DLP™) 4:3 or 16:9 Manual zoom & focus F=2.8~3.1 (f=31mm~40mm)
DISPLAY	Color Size Proj. Distance Lamp Brightness Contrast Ratio	16.7 Million 0.5588m-6.9342m (Diagonal) 1.0-10.0m 150W, OSRAM P-VIP 1000 ANSI Lumens 450:1
AUDIO	Speaker Power Frequency Response	1.97" x 0.71" (DxH), Circular x1 3.0W 150Hz-14kHz
INPUT SIGNAL	Video Sync Frequency	RGB Analog, NTSC, PAL, SECAM H/V Separated (TTL) fh:15-90 kHz; fv:50-85 Hz
COMPATIBILITY	PC Mac®2	PC and compatibles (from VGA up to 1024x768 non-interlaced) Power Mac™ up to 1024x768
CONNECTOR	RGB Video S-Video Audio In/Out	15-pin HD RCA x1 (composite) SVHS DIN Connector 3.5 mm Mini Stereo Plug
POWER	Voltage Consumption	AC 100-240 VAC 50/60Hz AutoSwitch 200W (typ)
CONTROLS	Physical Remote OSD	Power, on/standby, menu, auto/reset, source, enter Power/Standby, reset, mute, volume +/-, PIP, menu, source, arrow up, arrow left, arrow right, arrow down, freeze, keystone, zoom, in/out, resync, enter Brightness, contrast, keystone correction, color temperature, tint (video only), color (video only), image (PC input only), tracking, frequency, H/V position, auto-image, 8 language, audio, projection [front, rear, front ceiling, rear ceiling, PIP [On/Off], lamp, exit
OPERATING CONDITION	Temperature Humidity	50°F to 104°F (10°C to 40°C) 10% to 85% (non-condensation)
DIMENSIONS	Physical	90mm (W) x 252mm (D) x 218mm (H) 3.5" (W) x 9.9" (D) x 8.6" (H)
WEIGHT	Net	2.3 kg (5.0 lbs)
REGULATIONS		FCC-B, UL, cUL, CE, TUV/GS
ACCESSORIES		Power Cord, VGA 15 Pin 1.8m Cable, S-Video Cable, RCA Video Cable, Stereo RCA to Mini Stereo (3.5mm) Audio Cable, Mini Stereo (3.5mm) to Mini Stereo Audio Cable, Remote Control, Lens Cap, Soft Carrying Case ³



ViewSonic Corporation's QMS/EMS has been registered to ISO 9001 & ISO 14001 by the British Standards Institution.



www.ViewSonic-projectors.com

381 Brea Canyon Road, Walnut, CA 91789
 Toll Free (866) LITEBIRD (866) 548-8247 • (909) 869-7976
 Fax (909) 444-5698 • email: projectors@ViewSonic.com