ViewSonic[®] E70m/E70mB CRT Monitor 17" (16.0" VIEWABLE) E^{2®} SERIES CRT



Multimedia versatility, affordable quality.

The ViewSonic E70m and E70mB 17" (16.0" viewable) CRT monitors combine **PROFESSIONAL QUALITY AND RELIABILITY** in an affordable multimedia package. Easy-on-the-eyes 1024x768 optimum resolution and 0.23mm horizontal dot pitch deliver bright, crisp, precise images. Adjust your screen with the OnView[®] controls and secure them with the OSD lock function **ENSURING OPTIMUM SCREEN PERFORMANCE.** Increase desktop space and reduce clutter with integrated features such as bezel-integrated speakers. The E70m and E70mB are ideal for

education, Internet and business applications.

Award-Winning Company

ViewSonic is the #1 best-selling monitor brand in the USA, delivering price and performance leadership.*

Attractively affordable performance.

••••>0.23mm horizontal dot pitch 0.27mm diagonal dot pitch

This fine dot pitch produces clear, crisp images with precise picture definition, even at the highest resolutions.

Displays a maximum resolution of 1280x1024; 1024x768 at 87Hz flicker-free refresh rate for easy-on-the-eyes viewing.

---->OnView® controls

Screen adjustments are made via an on-screen menu using simple controls.

----->OSD lock function

When activated, user-controlled OSD lock function prevents changes to monitor settings, maintaining an optimized image.

··· Bezel-integrated speakers

Save desk space and clutter with the on-demand-audio, integrated speakers.

----->ViewSonic Wizard

This user-friendly Wizard software automates the set-up process to deliver optimized screen performance.

···· MPR II and ENERGY STAR[®] qualified

Effective power management reduces cost through automatic power saving modes.

- ----->Three-year limited warranty

24/7 free technical and customer support**.



Keep the style going with a matching ViewSonic keyboard – just one of many accessories available (sold separately).



ViewSonic[®] E70m/E70mB CRT Monitor 17" (16.0" VIEWABLE) E^{2®} SERIES CRT





- **1.** One-touch buttons control all major functions
- **2.** *Keep the style going with the attractive black case*
- **3.** OSD lock saves screen adjustments for optimal viewing

l	TANK I	Ě
ų		
		<

Available colors: Black (E70mB), Beige (E70m)



17" (16.0" VIEWABLE) CRT MONITOR WITH ONVIEW[®] CONTROLS

17 (10.0 VII	EVVADLE) CR	WORTOR WITH UNVIEW CONTROLS	
CRT	Type Dot Pitch Phosphor Glass Surface	17.0" (16.0" viewable) 90° deflection 0.23mm horizontal x 0.13mm vertical; 0.27mm diagonal RGB P22 medium persistence Tint: TM~52%, anti-static, anti-glare screen coating	
INPUT SIGNAL	Video Sync Frequency	RGB analog (75 ohms, 0.714 Vp-p) H/V separated (TTL) Fh:30~70kHz, Fy:50~160Hz	
COMPATIBILITY	PC Mac ^{®*}	VGA up to 1280x1024 non-interlaced Power Mac™ G3/G4 1024x768	
CONNECTOR	Analog Power	15 pin mini D-sub 3-pin plug (IEC320)	
POWER	Voltage Consumption	AC 100–240V, 50/60Hz 75W (typ)	
CONTROLS	Basic OnView [®]	Power, on/off, 1, down, up, 2, speaker mute Contrast, brightness, degauss, H./V. size, H./V. position, pincushion, pinbal- ance, trapezoid, parallelogram, tilt, moiré reduction, ViewMatch [®] color (9300K, 6500K, user), language, OSD position, zoom, recall and ViewMeter [®]	
VIDEO INPUT	Bandwidth	110MHz (typ)	
MISCONVERGENCE		0.25mm (max) at center 0.35mm (max) at corner	
DISPLAY AREA	Factory Setting Maximum Scan	310mm horizontal x 230mm vertical 320mm horizontal x 240mm vertical (dependent upon timing signal)	
OPERATING CONDITIONS	Temperature Humidity	32°—104°F (0°—40°C) 5—95% (no condensing)	
DIMENSIONS (W X H X D)	Physical	406mm x 417mm x 435mm 16.0" x 16.4" x 17.1"	
WEIGHT	Net Gross	35.7 lb. (16.2 kg) 39.9 lb. (18.1 kg)	
REGULATIONS		UL/cUL, DHHS, FCC-B, CB, ICES 003, Argentina - TUV/S, MPR II, ISO9241-3 7 8, NOM, ENERGY STAR [®]	
POWER MANAG	EMENT	Meets MPR II and ENERGY STAR [®] standards	
WARRANTY		Three-year limited warranty on CRT, parts and labor.	



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution



ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

Phone (800) 888-8583 or (909) 444-88888 • In Canada (866) 262-1967 • Fax (909) 839-7922 • SalesInfo@ViewSonic.com • ViewSonic.com *Leading stand-alone, branded monitor by sales (CRT and LCDs combined; iSuppli/Standord Resources Monitrak" and Fat Panel Monitrak,* 2024 Report) **Excludes major U.S. holidays, †Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country, see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2004 ViewSonic Corporation. All rights reserved. [12071-008-07/04] E70m/E70m/B-2

922 • SalesInfo@ViewSonic.com • ViewSonic.c be required. Analog adapter available from ViewSonic. Specifications subject to change without noti Copyright © 2004 ViewSonic Corporation. All rights reserved. [12071-008-07/04] E70m/E70mB-2

For more product information, visit us on the web at ViewSonic.com