ViewSonic[®] E75f Monitor

E^{2®} Series



This 17" (16.0" viewable) flat-screen CRT is sharp.

The ViewSonic E75f offers exceptional quality performance for demanding business and home office users seeking a sharp, reliable display solution. Featuring ViewSonic's award-winning PerfectFlat screen technology, the E75f renders brilliant, edge-to-edge, precise images with sharp focus and ultra-fine text. The E75f also incorporates SuperClear screen technology to enhance brightness and color fidelity for the most realistic images possible. And the OSD lock function prevents accidental or intentional changes to monitor fine-tuning. When sharp images and resolution flexibility are important; the ViewSonic E75f is an excellent choice.

• 0.21mm horizontal pitch, 0.25mm diagonal pitch

This ultra-fine dot pitch produces super clear, crisp images with great picture definition, even at the highest resolutions.

• 1600 x 1200 maximum resolution

Displays a maximum resolution of 1600 x 1200; 1280 x 1024 at 80Hz flicker-free refresh rate for easy viewing.

1600 x 1200 @ 68Hz 1280 x 1024 @ 80Hz 1024 x 768 @ 105Hz 800 x 600 @ 132Hz

PerfectFlat[®] Screen

Absolutely flat screen provides realistically proportioned, precise images with reduction of ambient light reflection, image distortion and eye fatigue.

SuperClear[™] Screen

SuperClear screen technology incorporates enhanced phosphor treatment and optimized glass to deliver vivid colors and image clarity.

• OnView[®] controls including OSD lock function

All screen adjustments are made via an onscreen menu using simple controls. The new OSD lock function prevents accidental changes to optimized monitor settings.

ViewSonic Wizard

The ViewSonic Wizard software provides userfriendly installation. The included CD-ROM automates the set-up process to deliver optimized screen performance.



ViewSonic[®] See the difference[®]

E^{2®} Series

ViewSonic[®]



Anti-static, anti-reflective screen

This anti-static, anti-reflective screen coating refracts unwanted light away from the user while maintaining the highest quality of the displayed image.

USB-compatible base

New base design allows easy integration of an optional ViewSonic USB (Universal Serial Bus) hub for convenient USB peripheral connections.

MPR II and Energy 2000 compliant

This monitor surpasses these strict standards for reduced emissions, power management and efficiency.

ViewSonic color management

Color management software including E-Color True Internet Color[®] for reliable colors when user's visit E-Corrected[™] web sites. Colorific[®] and ViewSonic's ViewMatch[®], ensure color matching from screen to other color peripherals such as color printers.

- Plug & Play +
- PC and Mac[®] compatible
- Three-year limited warranty 24/7 free technical and customer service.

E75f Monitor

17" (16.0" VIEWABLE) COLOR MONITOR

CRT	Туре	17" (16.0" diagonal viewable area), 0.21mm (H), 0.13mm (V), 0.25mm (D)
	Dot Pitch	90° deflection
	Phosphor	RGB P22 medium/short persistence
	Glass Surface	Anti-static, Anti-reflection, TM ~ 50%
ANALOG INPUT	Video	RGB Analog (75 ohms, 0.7/1.0 Vp-p)
	Sync	H/V Separated (TTL), composite
	,	f _H :30-86kHz; f _V :50-150Hz
COMPATIBILITY	РС	IBM and PC compatible from VGA up to 1600 x 1200
	Mac*	Power Mac (up to 1152 x 870)
CONNECTOR	Input Signal	15-pin mini D-sub (attached cable)
	Power	3-pin plug (IEC320)
POWER	Voltage	AC 100-264VAC (auto switch) 50-60Hz
	Consumption	90W (typ), 100X (max)
CONTROLS	Physical	Power, On/Off, 1, Up, Down, 2
	OSD	Contrast, brightness, H/V size, H/V position, pincushion,
		pin balance, trapezoid, parallel, rotation, degauss,
		ViewMeter [®] , zoom, H/V moire, language, ViewMatch [®] ,
		recall
VIDEO INPUT	Bandwidth	183MHz
DISPLAY AREA	Factory Setting	310mm (H) x 230mm (V)
OPERATING	Temperature	-40–140° F (-40°–60° C)
CONDITION	Humidity	5-95% (non-condensation)
DIMENSIONS	Physical	404mm (W) x 406mm (H) x 425mm (D)
	-	(15.9" x 16.0" x 16.7")
WEIGHT	Net	16.3Kgs (36 lbs)
REGULATIONS		UL, CSA, FCC-B, ICES-003, DHHS, MPR II, NOM, TUV/S,
		EPA Energy Star®, E2K
POWER MANAGEMENT		Meets Energy 2000 standards
WARRANTY		Three-year limited warranty on parts and labor.



to ISO 9001 & ISO 14001 by the British Standards Institution





See the difference.

381 Brea Canyon Road, Walnut, CA 91789 • Phone (800) 888-8583 or (909) 869-7976 • Fax (909) 869-7958 • ViewSonic.com

* Requires Mac cable adapter available. Corporate names and trademarks stated herein are the property of their respective companies. Specifications subject to change without notice. Copyright © 2001, Viewsonic Corporation. All rights reserved. VSE75f_08/01-10k [10270-00B 08/01] VS-2110