

# ViewSonic® E90fmb Monitor

*E<sup>2</sup>® Series*



## PerfectFlat 19" (18" viewable) multimedia monitor value.

The ViewSonic flat-screen E90fmb offers affordable value in a 19" (18.0" viewable) multimedia monitor. Featuring ViewSonic's award-winning PerfectFlat screen technology, the E90fmb renders precise, edge-to-edge images with sharp focus and minimized reflection. The ultra-fine 0.21mm horizontal dot pitch delivers sharp, easy-on-the-eyes viewing, and built-in 2-watt speakers, microphone and headphone jack provide computer telephony capabilities. The ViewSonic E90fmb, in stylish black, is the ideal choice for education, home and small office environments.

- **0.21mm horizontal pitch  
0.25mm diagonal pitch**

This ultra-fine dot pitch produces super clear, crisp images with great picture definition, even at the highest resolutions.

- **1600x1200 maximum resolution**

Displays a maximum resolution of 1600x1200; 1280x1024 at 80Hz flicker-free refresh rate for easy-on-the-eyes viewing.

1600 x 1200 @ 67Hz

1280 x 1024 @ 80Hz

1024 x 768 @ 102Hz

800 x 600 @ 130Hz

- **Bezel-integrated speakers and microphone**

Dual 2-watt built-in audio speakers save desk and work space while offering superior sound quality. Built-in microphone allows bi-directional communications in true multi-media applications such as video conferencing and computer telephony.

- **PerfectFlat® screen**

Absolutely flat screen provides realistically proportioned, precise images with reduced reflection, image distortion and eye fatigue.

- **SuperClear® technology**

SuperClear screen technology incorporates enhanced phosphor treatment and optimized glass to deliver vivid colors and image clarity.



**ViewSonic®**  
*See the difference.®*

# ViewSonic®

## E90fmb Monitor



### • OnView® controls

Screen adjustments are made via an on-screen menu using simple controls.

### • OSD lock

Prevents accidental misadjustments of OnView controls to maintain optimized image quality.

### • USB hub-compatible base

Base design allows easy integration of the optional ViewSonic USB (Universal Serial Bus) hub for convenient USB peripheral connections.

### • Headphone jack and external microphone port

### • ENERGY STAR® certified

### • Turn your monitor into a high-resolution TV

Hook up favorite extras like a DVD, gaming consoles, VCR or digital camera with ViewSonic's video processing box.



### 19" (18" VIEWABLE) PERFECTFLAT® COLOR MONITOR

CRT	<b>Type</b>	19" (18" viewable) CRT, 90° deflection
	<b>Dot Pitch</b>	0.21mm horizontal, 0.13mm vertical, 0.25mm diagonal
	<b>Phosphor</b>	RGB P22 medium persistence
	<b>Glass Surface</b>	Anti-reflection, anti-static coating; TM~46%
INPUT SIGNAL	<b>Video</b>	RGB analog (75 ohms, 0.714 Vp-p)
	<b>Sync</b>	H/V separated (TTL), composite
	<b>Frequency</b>	f <sub>h</sub> : 30~86kHz; f <sub>v</sub> : 50~150Hz
COMPATIBILITY	<b>PC</b>	PC compatible from VGA up to 1600 x 1200
	<b>Mac®*</b>	Power Mac™ up to 1152 x 870
INPUT CONNECTORS	<b>Video</b>	15-pin mini D-sub (attached)
	<b>Audio</b>	3.5mm pin mini jack (stereo)
	<b>Microphone</b>	3.5mm pin mini jack (mono/auxiliary)
	<b>Power</b>	3-pin plug (ICE320)
OUTPUT CONNECTORS	<b>Headphone</b>	3.5mm pin mini jack (stereo)
	<b>Microphone</b>	3.5mm pin mini jack (mono)
POWER	<b>Voltage</b>	AC 100~240V, 50~60Hz (auto switch)
	<b>Consumption</b>	110W (typ), 120W (max)
CONTROLS	<b>Basic</b>	Power, on/off, buttons 1, down, up, 2, speaker mute, volume down, volume up
	<b>OnView</b>	Contrast, brightness, zoom, H/V size, H/V position, pincushion, pin balance, trapezoid, parallel, tilt, H/V moiré, ViewMatch® color temperature (9300, 6500, user), degauss, memory recall, ViewMeter®, language, OSD lock
VIDEO INPUT	<b>Bandwidth</b>	175MHz (typ)
AUDIO	<b>Speaker</b>	2-watt + 2-watt @ 1KHz
	<b>Frequency</b>	100~20KHz
MISCONVERGENCE		0.25mm (max) at center; 0.30mm (max) at corner
DISPLAY AREA	<b>Factory Setting</b>	352mm (H) x 264mm (V) (typ) 13.9" x 10.4"
	<b>Maximum Scan</b>	365mm (H) x 274mm (V) (dependent on timing used) 14.4" x 10.8"
OPERATING CONDITIONS	<b>Temperature</b>	32~104° F (0~40° C)
	<b>Humidity</b>	5~95% (non-condensing)
DIMENSIONS	<b>Physical</b>	464mm (W) x 492mm (H) x 472mm (D) 18.2" x 19.3" x 18.5"
WEIGHT	<b>Net</b>	22.0 kgs. (48.5 lbs.)
	<b>Gross</b>	25.5 kgs. (56.2 lbs.)
REGULATIONS		UL, CSA, FCC-B, ICS-003, DHHS, NOM, TUV-S, ENERGY STAR®, MPR II
POWER MANAGEMENT		Meets ENERGY STAR®, MPR II standards
WARRANTY		Three-year limited warranty on CRT, parts and labor.



FM 40187



EMS 40968

ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.



**ViewSonic®**  
See the difference.®