

N4261w

42" WIDESCREEN 1080P LCD HDTV

WITH DUAL HDMI INPUTS

Amazing home entertainment.

ViewSonic's high-performance N4261w 42" widescreen LCD TV brings you images so stunning you'll never go back to standard TV again. COMPATIBILITY WITH 1080P VIDEO signals and the extremely high 1920x1080 panel resolution complement the already sharp digital images for the MAXIMUM IMAGE QUALITY. Advanced image processing, fast 8ms video response and wide viewing angles deliver blur-free images from virtually anywhere in the room. Connect HD set top boxes, DVD players, game consoles and more through the DUAL HDMI INPUTS and other video inputs. High brightness and 1500:1 CONTRAST RATIO (typ) deliver rich, vibrant colors. The SRS® TruSurround XT speakers bring theater-like surround sound to your home entertainment center.



LIFELIKE, HIGH-DEFINITION TV

> Experience widescreen HDTV

Enjoy a widescreen theater experience and high-definition picture quality with this display's widescreen aspect ratio, true HDTV capability, and wide viewing angles.

> Advanced image processing delivers clearer, crisper, sharper images

Advanced image processing eliminates noise, increases contrast and detail and optimizes color for rich, vibrant images. High-definition images look amazing and even standard television images are unbelievably smooth and sharp.

> Vivid graphics, clear text, stunning TV

Ultra-high brightness of 500 nits (typ), high contrast ratio of 1500:1 (typ), and 1920x1080 optimum resolution provide vibrant video and lifelike images.

> Expand your options with two HDMI inputs

Enjoy the ultimate viewing experience with integrated HDTV tuner and plug-and-play, high-end connectivity of two HDMI inputs for HD set-top boxes, standard and HD-DVDs, game consoles, Blu-Ray™ discs, camcorders and more.

> OptiSync® technology now features HDMI

Add versatility to your LCD TV with support for HDMI with high-definition content protection (HDCP) and analog (VGA) signals, plus component, S-video, composite, and TV/cable input.

> Powerful high-fidelity audio

It's all accompanied by an ultra-high fidelity 20-watt SRS TruSurround XT sound that completes the entertainment experience.



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

HDMI™
HIGH-DEFINITION MULTIMEDIA INTERFACE

SRS (O)
TruSurround XT

1080p
Full HD

ViewSonic®
See the difference® 

N4261w

42" WIDESCREEN 1080P LCD HDTV WITH DUAL HDMI INPUTS



| | | |
|-------------------------------|-------------------|---|
| LCD | Type | 42" color TFT active matrix, wide LCD |
| | Display Area | 36.6" horizontal x 20.6" vertical; 42.02" diagonal |
| | Native Resolution | 1920x1080 |
| | Contrast Ratio | 1500:1 (typ) |
| | Viewing Angles | 176° horizontal, 176° vertical |
| | Response Time | 8ms |
| | Light Source | Long life, 50,000 hrs. (typ) |
| | Brightness | 500 cd/m2 (typ) |
| | Aspect Ratio | 16:9 |
| | Glass Surface | Anti-glare, anti-reflective coat |
| | INPUT | PC |
| TV | | TV/cable, composite (RCA), component YPbPr/YCbCr, S-video |
| Audio | | 3.5mm mini stereo audio in/out and RCA (left/right) audio in |
| RGB Frequency | | F _H : 30~64kHz, F _V : 60~75Hz |
| Sync | | H/V separated (TTL) |
| Digital | | HDMI (with HDCP and audio support) |
| Tuner | | ATSC/NTSC |
| AUDIO OUTPUT | Speakers | 2x10-watt SRS TruSurround XT sound |
| COMPATIBILITY | PC | 1360x768 (preferred), 1024x768, 1280x768, 1280x1024, 1280x720 |
| | Mac®* | Power Mac™ G3/G4/G5 up to 1280x1024 |
| INPUT SIGNAL | TV/Video Comp. | 480i, 480p, 720p, 1080i, 1080p |
| CONNECTOR | Analog | 15-pin mini D-sub (VGA) |
| | Digital | HDMIx2 |
| | Power | 3-pin plug |
| POWER | Voltage | AC 90~240V (universal), 50~60Hz |
| | Consumption | 260W (typ) |
| CONTROLS | Basic | Power, enter, channel +/-, volume +/-, menu |
| | (Video Mode) | Contrast, brightness, color, tint, sharpness, smart picture mode; audio menu (bass, treble, balance, surround on/off, audio out on/off, digital audio out, digital audio language, smart sound mode); setup menu (language, parental, V-chip, color temperature, time zone, OSD timeout, memory recall) |
| | (TV Mode) | Tuner mode, auto scan, channel add/delete, channel name, channel close caption, digital cc style |
| | OnView® (PC Mode) | Auto adjust, contrast, brightness, H. position, V. position, fine tune |
| OPERATING CONDITIONS | Temperature | 32~104°F (0~40°C) |
| | Humidity | 10~90% (non-condensing) |
| DIMENSIONS (W x H x D) | Physical (mm) | 1070x815x305 |
| | | 1070x760x136 |
| | Physical (in.) | 42.1x32.1x12.0 |
| | | 42.1x29.9x5.3 |
| VESA® MOUNT | | 650mm x 400mm |
| WEIGHT | Net | 83.8 (38 kg) w/o stand 74.6 (32.6 kg) |
| | Gross | 99.2 (45 kg) |
| RECYCLE/DISPOSAL | | The lamp in this product contains mercury. Please dispose of in accordance with local, state and federal laws. |
| REGULATIONS | | cUL, FCC, NOM, EN 55013, CB |
| PACKAGE CONTENTS | | LCD TV display, power cable(s), remote control with batteries, VGA cable, RCA A/V cable, Quick Start Guide, User Guide |
| WARRANTY | | One-year limited warranty on parts and backlight |



ISO 9001:2000
FM 40187



ISO 14001:1996
FM 40968

ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

Customer Service and Technical Support: (800) 688-6688 • Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

*Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2007 ViewSonic Corporation. All rights reserved. [13421-00B-03/07] N4261w-1

ViewSonic®
See the difference®

For more product information, visit us on the web at ViewSonic.com