

ND4200-LS

42" HD PLASMA NETWORK DISPLAY

WITH INTEGRATED INTERNET PROTOCOL (IP) NETWORKING

Dynamic digital signage.

ViewSonic's ND4200-LS 42" HD network display is one of the first high-definition plasma displays with integrated industry standard Internet Protocol (IP) networking – another benchmark innovation by ViewSonic®. The ND4200-LS directly decodes video over IP and can be REMOTELY MANAGED FROM VIRTUALLY ANYWHERE IN THE WORLD via the Internet. ViewSonic brings its heritage of award-winning display and media networking technologies to the world of commercial digital signage. Especially designed for business installations, the ND4200-LS CUSTOMIZABLE DISPLAY CAN PLAY UNIQUE OR IDENTICAL CONTENT in multiple locations within a building, across a large business campus or even in diverse locations across the country. Brilliantly display call center information boards, window advertisements, transportation depot information, restaurant menus, and in-store merchandising.



VIDEO OVER IP – WIRED OR WIRELESS

- > Fully integrated IP enabled display provides easy network connection without a dedicated PC

Address and control display from anywhere via the Internet eliminating the need for an external PC or expensive video splitters and converters. Quickly add optional wireless operation or local storage with USB connection.

- > Easy audio video steaming with content-rich video and graphics
Display dynamic and captivating content with the included Macromedia Flash 6. Decodes MPEG-1/2/4, DivX and WMV9 audio/video formats. Precision digital audio for rich multimedia experience with optional detachable speakers sold separately.

- > Easy installation and simplified cabling

Connect multiple units together for even easier cabling and installation with loop through RJ-45 connections. Dual USB ports for loading content locally.

- > Lower total cost of ownership (TCO)

Eliminates local PC; simplified cabling and installation; easy-to-use software; remotely controlled, and higher reliability than Windows-based PC systems.

- > Commercial display solutions by ViewSonic

Customizable displays are specifically designed for point-of-sale advertisements, public information, training, menu boards, corporate communications and remote education.

- > Infrastructure is fully compatible with Cisco networks for robust performance



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

ViewSonic 

the choice of professionals


ND4200-LS

42" HD PLASMA NETWORK DISPLAY WITH INTEGRATED INTERNET PROTOCOL (IP) NETWORKING



Rear connectors:

- 1) Audio R/L
- 2) Dual USB
- 3) RJ-45 NET
- 4) RJ-45 LAN



| | | |
|-------------------------------|--------------------|---|
| PLASMA | Type | 42" color plasma |
| | Display Area | 36.7" horizontal x 21.0" vertical; 42.0" diagonal |
| | Optimum Resolution | 1024x768 |
| | Contrast Ratio | 3000:1 (typ) |
| | Viewing Angles | 160° horizontal, 160° vertical |
| | Brightness | 1000 cd/m2 (typ) |
| CONNECTOR | Aspect Ratio | 16:9 (native) |
| | Audio Output | 2xRCA stereo analog |
| | Network | 2xRJ-45 |
| DECODING | Communication | 2xUSB |
| | Video | MPEG-1, MPEG-2, MPEG-4, WMV9, Macromedia® Flash™ |
| LOCAL STORAGE/ MEMORY | Audio | MPEG-1 (layers 1 & 2), MP3, WMA, WAV |
| | | 40GB hard drive |
| STREAMING | Types | HTTP, VDP, RTP, IP/TV, local file playback |
| PROTOCOL | | |
| IMAGE FILES | Formats | JPEG |
| AUDIO OUTPUT | Speakers | 2x12-watt (optional) |
| SCANNING FORMAT | | SDTV 480i, EDTV 480p, HDTV 720p, 1080i |
| POWER | Voltage | AC 100–240V (max), 50/60Hz |
| | Consumption | 390W (typ) |
| OPERATING CONDITIONS | Temperature | 41–104°F (5–40°C) |
| | Humidity | 20–85% (non-condensing) |
| DIMENSIONS (W x H x D) | Physical (mm) | 1015mm x 613mm x 67.5mm |
| | Physical (in.) | 40.0" x 24.1" x 2.7" |
| WEIGHT | Net | 86.0 lb. (39.1 kg) |
| | Gross | 99.0 lb. (45.0 kg) |
| REGULATIONS | | UL, cUL, FCC, Part 15 Class B, IC |
| PACKAGE CONTENTS | | Plasma display, power cable, Ethernet cable (6 ft.), remote control with batteries, Quick Start Guide, User Guide |
| OPTIONAL ACCESSORIES | | Wireless USB adapter, wall mount, detachable speakers |
| WARRANTY | | One-year limited warranty on parts and labor |



ISO 9001:2000
FM 40187



ISO 14001:1996
FM 40968

ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

ViewSonic

the choice of professionals

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

Customer Service and Technical Support: (800) 688-6688 • Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2006 ViewSonic Corporation. All rights reserved. [12760-01B-07/06] ND4200-1

For more product information, visit us on the web at ViewSonic.com