PJ258D

MICRO-PORTABLE VIEWDOCK[™] PROJECTOR

FEATURING IPOD® WITH VIDEO DOCK

Digital lifestyle iPod[®] projector

ViewSonic's PJ258D ViewDock[™] projector sets the bar for digital lifestyle projectors for work and play by converging entertainment excitment with professional practicality. The integrated iPod dock lets you PROJECT CONTENT DIRECTLY FROM YOUR IPOD WITH VIDEO for larger-than-life pictures and videos. The array of projector connectivity options allows you to connect a PC, DVD player, game consoles, and more. The PJ258D uses Texas Instruments DLP[®] technology for RAZOR SHARP DIGITAL IMAGES and brilliantly displays 2,000 lumens for use in virtually any setting. Its stylishly contoured design is sophisticated for the contemporary professional on the go and the entertainment aficionado by night. Your projector doesn't have to be lackluster anymore as ViewSonic's PJ258D ViewDock[™] elevates the status of your digital lifestyle.



Made for

iPod

6

DLP

TEXAS INSTRUMENTS

LIFE-SIZE YOUR IPOD

- > Bright in virtually any setting with 2,000 lumens Packs 2,000 lumens in just 2.9 lbs. It's the bright choice for mobile presenters.
- > Life-size your iPod® with video

Dock and charge your iPod with video in the projector's docking station. Share your videos, podcasts, games and presentations in larger-than-life fashion.

> DLP[®] technology

Stunning all-digital clarity delivers lifelike color, sharp graphics, and outstanding video.

> Ultimate video source flexibility

Connect a computer or add a video source for dynamic meetings and presentations.

- Supports HD signals including 720p and 1080i Capable of displaying HD signals as well as other video and data sources.*
- > Unplug and go

Direct off feature lets you unplug the projector and go.

The best warranty in the business

Covered by a three-year parts and labor limited warranty, first-year Express Exchange® and one-year limited lamp warranty.***



PRODUCTS, PROGRAMS, AND SERVICES



PJ258D MICRO-PORTABLE VIEWDOCKTM PROJECTOR WITH IPOD[®] DOCK







Optional Accessories

- Replacement lampRLC-025
- Rolling soft case with notebook bag . .CASE-006
- Extended Express Exchange®PRJ-EE-03-03
- VGA to component video adapter . . . ADPT-002
- Wireless G presentation adapter WPG-100

| PROJECTOR | Туре | 0.55" DDR DMD, DLP® |
|------------------|-------------------------|---|
| | Pixel Format | 1024x768 XGA |
| | Lens | Manual zoom, manual focus |
| | Zoom Factor | 1.2 |
| | Keystone | Vertical $\pm 15^{\circ}$ |
| DISPLAY | Size | 40"-300" (diagonally) |
| | Throw Distance | 62.4"-468" |
| | Throw Ratio | 1.94-2.27:1 |
| | Lamp | 200W, 2,000 hours normal, up to 3000** hours eco |
| | Brightness | 2,000 ANSI lumens (max) |
| | Contrast Ratio | 2000:1 (max) |
| | | |
| | Aspect Ratio | 4:3 (native), 16:9 |
| AUDIO | Speakers | 1x1-watt |
| INPUT SIGNAL | Computer and Video | RGB analog, NTSC M, NTSC 4.43, PAL (B, D, G, H, I, M, N60), |
| | | SECAM (B, D, G, K, K1, L), 480i, HDTV (720p, 1080i) |
| | Frequency | F _h : 31.5–79.8kHz; F _v : 56–85Hz |
| COMPATIBILITY | PC | Analog: from VGA to SXGA (scaled) |
| | Mac®† | Analog: to SXGA (may require a Mac adapter) |
| CONNECTOR | RGB (input) | 15-pin HD, D-sub cable |
| | Composite Video (input) | RCA jack (x1) |
| | S-Video (input) | Mini-Din 4-pin (x1) |
| | Component Video (input) | |
| | iPod | Dock |
| POWER | Voltage | 100–240 VAC, 50/60Hz (universal) |
| | Consumption | 280W (typ) |
| CONTROLS | Basic | Standby/On, input, menu |
| | OnView [®] | Display (mode, brightness, contrast, white intensity, color |
| | 01111011 | temp, saturation), management (menu location, projection, |
| | | keystone, source lock, high altitude, translucence, reset), |
| | | frequency, phase, H. position, V. position, degamma, |
| | | |
| | | aspect ratio, V. shift 16:9, OSD language, color setting, |
| | | lamp setting |
| OPERATING | Temperature | 32°-104°F (0-40°C) |
| CONDITIONS | Humidity | 10-90% (non-condensing) |
| NOISE LEVEL | Normal | 37 dB (typ) |
| | Whisper Mode | 34 dB (typ) |
| DIMENSIONS | Physical (mm) | 288mm x 190mm x 83mm |
| (W x H x D) | Physical (in.) | 11.3" x 7.5" x 3.5" |
| WEIGHT | Net | 3.9 lb. (1.8 kg) |
| | Gross | 10.1 lb. (4.6 kg) |
| REGULATIONS | | UL, C-UL, FCC-B, CB, CE, TUV/GS, CCC, PSB, NOM |
| OTHER | | Whisper mode, iPod dock, optical zoom, wireless remote |
| | | control, soft carrying case, progressive scan, direct off for |
| | | unplug and go, daylight mode |
| PACKAGE CONTENTS | | iPod dock, projector, power cords, VGA cable, RCA video |
| | | cable, remote control, soft case, lens cap, ViewSonic |
| | | Wizard CD, Quick Start Guide |
| WARRANTY | | Three-year limited warranty on parts and labor, first-year |
| | | Express Exchange® Service. One-year limited warranty on |
| | | lamp*** |
| | | lamp |



ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789



Customer Service and Technical Support: (800) 688-6688 • Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com *Optional cables required. **Running whisper-mode exclusively can extend lamp life. ***Visit ViewSonic.com for full details. †Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs vary by country. See your ViewSonic representative for complete details. DLP is a registered trademark of Texas Instruments Inc. in the United States and other countries. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2007 ViewSonic Corporation. All rights reserved. [13471-00B-04/07] PJ258D-1

For more product information, visit us on the web at ViewSonic.com