

PJ558D

LIGHT, BRIGHT AND PORTABLE PROJECTOR

WITH KEYSTONE CORRECTION

Bright DLP® projector.

ViewSonic's PJ558D projector features DLP® technology that delivers amazingly crisp digital images. With 2,500 LUMENS AND AN ULTRA-HIGH 2000:1 CONTRAST RATIO (TYP) this portable projector lets you deliver multimedia lessons in the classroom or dynamic presentations in the boardroom with stunning visual impact. The native 1024x768 XGA resolution, DIGITAL KEYSTONE CORRECTION AND OPTICAL ZOOM LENS ensure that you'll get the best possible image in virtually any setting. Experience the flexibility of the PJ558D thanks to SUPPORT FOR 720P AND 1080I HD SIGNALS, advanced video features and multiple inputs. It's a lightweight, powerful projector that lets you take your presentations to a new and brighter level in the office, on the road or in schools.



VISUALLY APPEALING MULTIMEDIA PRESENTATIONS

- > **Bright in virtually any setting with 2,500 lumens**
Packs 2,500 lumens in just 5.4 lb. It's the bright choice for mobile presenters.
- > **DLP® technology**
Stunning all digital clarity delivers lifelike color, sharp graphics, and outstanding video.
- > **Ultimate video source flexibility**
Connect a computer or add a video source for dynamic meetings and presentations.
- > **Supports HD signals including 720p and 1080i**
Capable of displaying HDTV signals as well as other video and data sources*.
- > **Advanced video features**
Motion adaptive deinterlacer for superior video performance.
- > **Whisper-mode extends lamp life**
Extend the life of your lamp up to 3,000 hours** and reduce noise output.
- > **OnView® controls for superior screen adjustability**
Screen geometry and color adjustments are precisely made via an easy-to-use, on-screen menu.
- > **The best warranty in the business**
Covered by a three-year parts and labor limited warranty, first-year Express Exchange® and one-year limited lamp warranty.***



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

ViewSonic®
See the difference® 

PJ558D

LIGHT, BRIGHT AND PORTABLE PROJECTOR WITH KEYSTONE CORRECTION



Optional Accessories

- Replacement lampRLC-023
- Stackable ATA hard shipping case ...CASE-003
- Hard case with wheelsPRJ-HCA-001
- Extended Express Exchange®PRJ-EE-05-03
- Soft case with wheelsCASE-006
- Universal ceiling mount kitWMK-005
- VGA to component video adapter ...ADPT-002
- Wireless G Presentation Gateway ...WPG-100



PROJECTOR	Type	0.55" DDR DMD, DLP®
	Pixel Format	1024x768 XGA
	Lens	Manual zoom/manual focus
	Zoom Factor	1.2
	Keystone	Vertical ± 15°
DISPLAY	Size	30"-300" (diagonally)
	Throw Distance	46.8"-393.6"
	Throw Ratio	1.64-1.96:1
	Lamp	230W, 2,000 hours**
	Brightness	2,500 ANSI lumens
	Contrast Ratio	2000:1
	Aspect Ratio	4:3 (native), 16:9
AUDIO	Speakers	1x2 watts
INPUT SIGNAL	Computer and Video	NTSC, NTSC 4.43, PAL, SECAM, RGB analog, HDTV (480i, 480p, 576i, 576p, 720p, 1080i)
	Frequency	F _H : 31-79kHz; F _V : 56-85Hz
COMPATIBILITY	PC	Analog: from VGA up to SXGA (scaled)
	Mac®†	Analog: up to SXGA (may require a Mac adapter)
CONNECTOR	RGB (input)	15-pin HD, D-sub cable (x1)
	RGB (output)	15-pin HD, D-sub cable (x1)
	Composite Video (input)	RCA jack (x1)
	S-Video (input)	Mini-Din 4-pin (x1)
	Component Video (input)	VGA DB-15 to HDTV/component cable*
	Audio (input)	Stereo mini-jack (x1)
	CONTROL POWER	Voltage
	Consumption	250W (typ)
CONTROLS	Basic	Standby/On, input, menu
	OnView®	Display mode, brightness, contrast, keystone, aspect ratio, blank screen, gamma, white peaking, color temperature, user color, video (sharpness, saturation, tint), display (phase, tracking, H. position, V. position), advance (auto source select, rear, ceiling, eco mode, lamp hours, lamp reset, auto shutdown, OSD timeout, menu position, factory reset), audio (audio, mute)
OPERATING CONDITIONS	Temperature	32-104°F (0-40°C)
	Humidity	10-90% (non-condensing)
NOISE LEVEL	Normal/Whisper mode	37 dB (typ)/32 dB (typ)
DIMENSIONS (W x H x D)	Physical (mm)	264mm x 203mm x 96.5mm
	Physical (in.)	10.4" x 3.8" x 8"
WEIGHT	Net	5.4 lb. (2.5 kg)
	Gross	12 lb. (5.4 kg)
REGULATIONS		UL, FCC-B, NOM, C-UL, ICES-003, TUV-S, RoHS
OTHER		Vertical digital keystone correction, 3:2 pull down, whisper mode
PACKAGE CONTENTS		Projector, power cord, VGA cable, RCA video cable, S-video cable, remote control, soft case, lens cap, ViewSonic Wizard CD, Quick Start Guide
WARRANTY		Three-year limited warranty on parts and labor, first-year Express Exchange® Service. One-year limited warranty on lamp***

ViewSonic®
See the difference® 

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

Customer Service and Technical Support: (800) 688-6688 • Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

*Optional cables required. **Running whisper-mode exclusively can extend lamp life. ***See ViewSonic.com for details. †Adapter may be required. Analog adapter available from ViewSonic. The DLP logo is a trademark of Texas Instruments. Specifications subject to change without notice. Selection, offers and programs vary by country. See your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2006 ViewSonic Corporation. All rights reserved. [13457-00B-03/07] PJ558D-1

For more product information, visit us on the web at ViewSonic.com