ViewSonic® Q190mb LCD Display

19" OPTIQUEST® SERIES LCD



Bright, versatile, slim bezel LCD display.

The ViewSonic Q190mb 19" LCD display enhances your productivity with its SuperClearMVA™ and OptiSync® technologies. SuperClearMVA delivers 700:1 contrast ratio (typ), high brightness, and 170° viewing angles to **ELEVATE YOUR IMAGES TO OUTSTANDING LEVELS** of sharpness and color. OptiSync technology **ENHANCES** YOUR CONFIGURATION FLEXIBILITY with support for analog and digital connectivity. The stylish, slim-bezel features an integrated power supply and built-in 2watt speakers for a multimedia display that saves desktop space.

Award-Winning Company

ViewSonic is the #1 best-selling monitor brand in the USA, delivering price and performance leadership.*



Enhance your productivity with style.

----- OptiSync® digital/analog inputs expand your connectivity

Multi-mode input technology supports both digital (DVI) and analog (VGA) signals for ultimate compatibility and configuration flexibility.

··· Multimedia enhanced

Save desk and workspace with dual 2-watt built-in stereo speakers.

… SuperClearMVA™ technology

Delivers high contrast, brilliant color, improved viewing angles and superior clarity for full-motion images.

*** **XtremeView** ultra-wide viewing angles extend your view

···* Stylish slim-bezel design

The full 19" viewable screen in an ultra-thin bezel lets you see more without taking up valuable desktop real estate.

··· High brightness and contrast

250-nit brightness (typ) and 700:1 contrast ratio (typ) for rich, detailed images.

··· Integrated power supply

- ---> Full 19" viewable screen
- ••• 1280x1024 resolution
- ···* OnView® controls for superior screen adjustability
- ···* Fold-up base for easy wall mounting
- **···**MPR II and ENERGY STAR® qualified
- ***** PC** and Mac[®] compatible



Keep the style going with a matching keyboard - just one of many accessories available for the Q190mb (sold separately).





ViewSonic® Q190mb LCD Display

19" OPTIQUEST® SERIES LCD





- 1. OnView® buttons control all major functions
- 2. Keep the style going with the attractive black case
- 3. Anti-static, anti-glare screen reduces eye-strain

19" COLOR LCD DISPLAY WITH SUPERCLEARMVA™ TECHNOLOGY

| 19" COLOR LO | CD DISPLAY V | NITH SUPERCLEARMVA™ TECHNOLOGY |
|---------------------------|--|---|
| LCD | Type Display Area Optimum Resolution Contrast Ratio Viewing Angles Response Time Light Source Brightness Panel Surface | 19" color TFT active matrix SXGA LCD 14.8" horizontal x 11.9" vertical; 19.0" diagonal 1280x1024 700:1 (Typ) 170° horizontal, 170° vertical 25ms (typ) Long life, 40,000 hrs. (typ) 250 cd/m2 (typ) Anti-glare |
| INPUT SIGNAL | Video Sync Frequency | RGB analog (75 ohms, 0.7 Vp-p); DVI-D (TMDS, 100 ohms) H/V separated (TTL) FH:30~80kHz, FV:50~75Hz |
| COMPATIBILITY | PC Mac | VGA up to 1280x1024 non-interlaced Power Mac™ G3/G4 1280x1024 |
| CONNECTOR | Analog Power | 15-pin mini D-sub and DVI-D AC in AC to head |
| POWER | Voltage Consumption | AC 100–240V (universal) 55W (max) |
| CONTROLS | Basic OnView* | Power, 1, down, up, 2 Auto image adjust, brightness, contrast, ViewMatch® color adjust (9300K, 6500K, 5400, user color), information (resolution, H. frequency, V. frequency, pixel clock, model number, serial number), image adjust (H. size, H. position, V. position, fine tune, sharpness), setup menu, language (English, French, German, Italian, Spanish, Finnish, Japanese, Traditional Chinese, Simplified Chinese), resolution notice, OSD position, OSD timeout, input select, memory recall, audio menu (volume, mute) |
| OPERATING CONDITIONS | Temperature Humidity | 32–104°F (0–40°C) 10–90% (no condensing) |
| DIMENSIONS (W x H x D) | Physical | 418mm x 413mm x 179mm 16.5" x 16.2" x 7.0" |
| WEIGHT | Net Gross | 12.3 lb. (5.6 kg) 15.6 lb. (7.1 kg) |
| REGULATIONS | | UL, cUL, FCC-B, CB, , ENERGY STAR®, NOM, TUV, MPR II, |
| POWER MANAG | EMENT | Meets MPR II and ENERGY STAR standards |
| WARRANTY | | Three-year limited warranty on parts, labor and backlight |





ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.



ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

Phone (800) 888-8583 or (909) 444-8888 • In Canada (866) 262-1967 • Fax (909) 839-7922 • SalesInfo@ViewSonic.com • ViewSonic.com

Leading stand-alone, branded monitor by sales (CRT and LCDs combined; Suppli/Stanford Resources Monitrak and Flat Panel Monitrak, * 2Q03 Report) **Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2004 ViewSonic Corporation. All rights reserved. [11908-01B-07/04] Q190mb-1