## Optiquest Q191wb

19" WIDESCREEN LCD

WITH FAST 5MS VIDEO RESPONSE

### Widescreen enhances productivity.

The Optiquest® Q191wb 19" widescreen LCD enhances your productivity because it lets you WORK IN TWO APPLICATIONS OR DOCUMENTS SIDE-BY-SIDE. Enjoy the crystal-clear, blur-free video and graphics delivered by broadcast-quality, 5MS VIDEO RESPONSE. High brightness and contrast ratios ensure your colors are rich and vibrant. The integrated power supply and VESA® wall-mount compliance reduce clutter and free up valuable desktop real estate. The OSD lock ensures your screen settings are secure and the Kensington® security port provides theft deterrence. Furnish your workplace in style with the budget-friendly, feature-rich Q191wb LCD.



### AN AFFORDABLE DISPLAY WITH STYLE AND PERFORMANCE

- > Fast 5ms video response delivers superior picture clarity
- > High brightness and contrast ratio
  270-nit brightness (typ) and 650:1 contrast ratio (typ) for rich, detailed images.
- > 1440x900 optimum resolution
  Incredible image detail for sharp text and graphics.
- > Stylish slim-bezel design

  An ultra-thin bezel lets you see more without taking up valuable desktop real estate.
- OnView® controls for superior screen adjustability Screen adjustments are precisely made via an easy-to-use on-screen menu.
- > Full 19" viewable widescreen

  Displays a full, flat 19" viewable area with crisp detail and fully saturated color.
- > Integrated power supply
- > VESA® 100mm wall-mount compliant
- > 24/7 free technical and customer support.\*
- > PC and Mac® compatible





# Optiquest Q191wb

#### 19" WIDESCREEN LCD WITH FAST 5MS VIDEO RESPONSE





LCD	Type	19" color TFT active matrix WXGA LCD
	Display Area	16.1" horizontal x 10.0" vertical; 19.0" diagonal
	Optimum Resolution	1440×900
	Contrast Ratio	650:1 (typ)
	Viewing Angles	170° horizontal, 160° vertical @ contrast ratio > 5:1
	Response Time	5ms (typ)
	Light Source	Long life, 50,000 hrs. (typ)
	Brightness	270 cd/m2 (typ)
	Panel Surface	Anti-glare
INPUT SIGNAL	Video	RGB analog (75 ohms, 0.7 Vp-p)
	Sync	H/V separated (TTL)
	Frequency	F <sub>h</sub> : 30~82kHz, F <sub>v</sub> : 50~85Hz
COMPATIBILITY	PC	VGA up to 1440x900 non-interlaced
	Mac®**	Power Mac™ G3/G4/G5 up to 1152x870
CONNECTOR	Analog PC	15-pin mini D-sub
	Power	3-pin AC plug (CEE22)
POWER	Voltage	AC 100–240V (universal), 50/60Hz (auto switch)
	Consumption	33W (typ)
CONTROLS	Basic	Power, 2, up, down,1
	OnView <sup>®</sup>	Auto image adjust, brightness, contrast, ViewMatch® color adjust
		(sRGB, 9300K, 6500K, 5400K user color), H. position, V. position,
		H. size, resolution notice, OSD position, OSD timeout,
		OSD background, fine tune, sharpness, language, recall,
		volume, mute
OPERATING	Temperature	41–95°F (5–35°C)
CONDITIONS	Humidity	20–85% (non-condensing)
DIMENSIONS	Physical with stand	17.7" x 14.5" x 6.7" (450mm x 368mm x 169mm)
(W x H x D)	Physical without stand	17.7" x 12.2" x 2.3" (450mm x 309mm x 58mm)
WEIGHT	Net with stand	9.6 lb. (4.4 kg)
	Gross with stand	13.0 lb. (5.9 kg)
REGULATIONS		UL, cUL, FCC-B, ENERGY STAR®, TCO-03, ICES-003B, RoHS,
		CB, CE, WEEE, ISO13406-2, TUV-S, NOM, GOST-R
POWER MANAGEMENT		Meets TCO'03 and ENERGY STAR® standards
PACKAGE CONTENTS		LCD display, power cable, video cable, Quick Start Guide, Wizard CD-ROM
WARRANTY		One-year limited warranty on parts and backlight









ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.



the choice of professionals

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

Customer Service and Technical Support: (800) 688-6688 • Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

\*Excluding major U.S. holidays. \*\*Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2006 ViewSonic Corporation. All rights reserved. [13194-01B-12/06] Q191wb-1