VA1903wb

19" VALUE SERIES WIDESCREEN LCD

WITH 5MS VIDEO RESPONSE

Expansive desktop performance.

ViewSonic's 19" VA1903wb LCD brings panoramic widescreen performance to the desktop at an affordable price. The widescreen aspect ratio and high 1440x900 resolution make it easy to view multiple document windows and side-by-side full page layouts. FAST CLEARMOTIV[®] 5MS VIDEO RESPONSE and 700:1 contrast ratio (typ), deliver IMMERSIVE GAMING with no blurs or ghosting, extreme clarity, amazing color and stunning brightness. The VA1903wb delivers on ViewSonic's tradition of BRILLIANT IMAGE QUALITY AND RELIABLE PERFORMANCE all at a budget-friendly price. It's the right choice for gamers, home/small office users and corporate professionals.

ENHANCE YOUR WORK AND PLAY

- > Fast 5ms video response delivers superior picture clarity
- Full 19" viewable widescreen Displays a full, flat 19" viewable area with crisp detail and fully saturated color.
- > 1440x900 native resolution Incredible image detail for sharp text and graphics.
- > High brightness and contrast 300-nit brightness (typ) and 700:1 contrast ratio (typ) for rich, detailed images.
- > Stylish slim-bezel design An ultra-thin bezel lets you see more without taking up valuable desktop real estate.
- > OSD/power lock secures your settings Prevents changes to monitor settings and maintains an optimized image.
- > OnView[®] controls for superior screen adjustability Screen adjustments are precisely made via an easy-to-use on-screen menu.
- Integrated power supply
- > ViewSonic Wizard included User-friendly Wizard software automates the setup process to deliver optimized
- > PC and Mac[®] compatible

screen performance.

> TCO'03 and ENERGY STAR® qualified



VIEWSONIC PRODUCTS, PROGRAMS, AND SERVICES

ViewSonic See the difference[®]





VA1903wb 19" VALUE SERIES WIDESCREEN LCD WITH 5MS VIDEO RESPONSE











ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

LCD	Туре	19" color TFT active matrix WXGA+ LCD
	Display Area	16.1" horizontal x 10.0" vertical; 19.0" diagonal
	Optimum Resolution	1440×900
	Contrast Ratio	700:1 (typ)
	Viewing Angles	160° horizontal, 160° vertical @ contrast ratio > 5:1
	Response Time	5ms (typ)
	Light Source	Long life, 50,000 hrs. (typ)
	Brightness	300 cd/m2 (typ)
	Aspect Ratio	16:9
	Panel Surface	Anti-glare
VIDEO INPUT	Analog	RGB analog (75 ohms, 0.7 Vp-p)
	Frequency	F _h : 24~82kHz, F _v : 50~75Hz
	Sync	H/V separated (TTL)
COMPATIBILITY	PC	VGA up to 1440x900 non-interlaced
	Mac®∗	VGA up to 1440x900 non-interlaced
CONNECTOR	Analog	15-pin mini D-sub
	Power	3-pin AC plug (CEE22)
POWER	Voltage	AC 100–240V (universal), 50/60Hz (auto switch)
	Consumption	34W (typ)
CONTROLS	Basic	Power, 1, down, up, 2
	OnView®	Auto image adjust, contrast, brightness, ViewMatch® color
		adjust (sRGB, 9300K, 6500K – default, 5400K, RGB), information
		(resolution, H-freq, V-freq, pixel clock, model number, serial
		number, web site), manual image adjust (H. size, H. position,
		V. position, fine tune, sharpness), setup menu (language,
		resolution notice, OSD position, OSD timeout, OSD back-
		ground), memory recall
OPERATING	Temperature	32–104°F (0–40°C)
CONDITIONS	Humidity	10–90% (non-condensing)
DIMENSIONS	Physical with stand	17.6" x 17.1" x 8.3" (448mm x 403mm x 210mm)
(W x H x D)	Physical without stand	17.6" x 12.9" x 2.4" (448mm x 318mm x 63mm)
WEIGHT	Net with stand	10.4 lb. (4.7 kg)
	Net without stand	6.38 lb. (2.9 kg)
	Gross with stand	13.2 lb. (6.0 kg)
REGULATIONS		UL, cUL, FCC-B, CB, CE, NOM, TUV/GS, TUV/ERGO
		(covers ISO13406-2), TCO'03, BSMI, CCC, ENERGY STAR,®
		PSB, C-TICK, RoHS, WEEE, VCCI, GOST-R, SASO
POWER MANAG	EMENT	
POWER MANAG PACKAGE CONT		PSB, C-TICK, RoHS, WEEE, VCCI, GOST-R, SASO
		PSB, C-TICK, RoHS, WEEE, VCCI, GOST-R, SASO Meets TCO'03 and ENERGY STAR® standards



ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

Customer Service and Technical Support: (800) 688-6688 • Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com *Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2007 ViewSonic Corporation. All rights reserved. [13300-01B-03/07] VA1903wb-1

For more product information, visit us on the web at ViewSonic.com