

VA1930wm

19" WIDESCREEN HEIGHT ADJUST LCD

WITH CLEARMOTIV® 5MS VIDEO RESPONSE

Big screen performance.

The ViewSonic® 19" VA1930wm features widescreen, multimedia performance at an affordable price. Ideal for use when you need a wider area to see all your work. The widescreen lets you work in two documents side-by-side. Gamers and graphics professionals will love the FAST 5MS VIDEO RESPONSE that delivers blur-free, full-motion video and crystal-clear graphics. OPTISYNC® ANALOG AND DIGITAL INPUTS provide versatile connectivity options. The INTEGRATED AMP AND STEREO SPEAKERS give you a complete multimedia experience. Make the most of your work space by mounting the VA1930wm on your wall. Choose the VA1930wm widescreen, multimedia display for a complete visual display experience on your desktop.



ENHANCE PRODUCTIVITY WITH A WIDESCREEN

- > **ClearMotiv® 5ms video response time**
Fast 5ms video response delivers broadcast-quality, full-motion video.
- > **Dynamic Structure™ technology**
Innovative liquid crystal composition and pixel matrix accelerate video response for seamless video and intense graphics.
- > **OptiSync® digital/analog inputs expand your connectivity**
Multi-mode input technology supports both digital (DVI) and analog (VGA) signals for ultimate compatibility and configuration flexibility.
- > **Ergonomic base adds ease and comfort**
Ultimate ergonomic flexibility comes built-in with the convenient 3.2" height adjustment, tilt and 360° swivel.
- > **Multimedia enhanced**
Save workspace and enjoy rich, stereo sound with two built-in stereo speakers.
- > **Stylish slim-bezel design**
The full 19" viewable widescreen in an ultra-thin bezel lets you see more without taking up valuable desktop real estate.
- > **High 300 nit brightness (typ) and 700:1 contrast ratio (typ)**
- > **VESA® 75mm wall mount interface and Kensington® security port**
- > **Windows Vista approved**
- > **PC and Mac® compatible**
- > **TCO'03 and ENERGY STAR® qualified**



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

ViewSonic®
See the difference® 

VA1930wm

19" WIDESCREEN HEIGHT ADJUST LCD WITH CLEARMOTIV® 5MS VIDEO RESPONSE



360° SWIVEL



HEIGHT ADJUST



TILT



ISO 9001:2000
FM 40187



ISO 14001:1996
FM 40968

ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

Customer Service and Technical Support: (800) 688-6688 • Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

*Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Windows Vista and the Windows Vista logo are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2007 ViewSonic Corporation. All rights reserved. [13368-00B-01/07] VA1930wm-1

LCD	Type	19" color TFT active matrix SXGA+ LCD
	Display Area	16.1" horizontal x 10.1" vertical; 19" diagonal
	Optimum Resolution	1440x900
	Contrast Ratio	700:1 (typ)
	Viewing Angles	160° horizontal, 160° vertical @ contrast ratio > 10:1
	Response Time	5ms (typ)
	Light Source	Long life, 50,000 hrs. (typ)
	Brightness	300 cd/m2 (typ)
	Panel Surface	Anti-glare
	VIDEO INPUT	Analog/Digital
Frequency		F _H : 24~82kHz, F _V : 50~75Hz
Sync		H/V separated (TTL)
COMPATIBILITY	PC	VGA up to 1440x900 non-interlaced
	Mac**	Power Mac™ G3/G4/G5 up to 1440x900
CONNECTOR	Analog/Digital	15-pin mini D-sub/DVI-D
	Audio In	Stereo mini audio line in
	Power	3-pin AC plug
POWER	Voltage	AC 100~240V (universal)
	Consumption	35W (typ)
AUDIO	Speakers	2x1.5-watt
	Amplifier	1.5-watt @ THD < 8%
CONTROLS	Basic	Power, 1, down, up, 2, mute, volume +/-
	OnView®	Auto image adjust, brightness, contrast, input selection, ViewMatch® color adjust (sRGB, 9300K, 6800K, 6500K), information (mode, model number, serial number), audio (volume, mute), manual image adjust (H. position, V. position, fine tune, sharpness), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), memory recall
ERGONOMICS		Height adjustment range 3.2", tilt, swivel range 360°
OPERATING	Temperature	41~95°F (3~35°C)
CONDITIONS	Humidity	20~80% (non-condensing)
DIMENSIONS	Physical with stand	18.1" x 17.1" x 9.1" (460mm x 434mm x 230mm)
	Physical without stand	18.1" x 13.9" x 2.4" (460mm x 352mm x 61mm)
WEIGHT	Net with stand	11.9 lb. (5.4 kg)
	Net without stand	9.6 lb. (4.4 kg)
	Gross with stand	15.2 lb. (6.9 kg)
REGULATIONS		UL, cUL, FCC-B, ICES-003, CB, CE, ENERGY STAR®, NOM, TUV/GS, Argentina TUV-S, TUV/ERGO (covers ISO13406-2 & MPR II), TCO'03, GOST-R, SASO, PCBC, VCCI, BSMI, CCC, MIC, PSB, C-TICK, RoHS
RECYCLE/DISPOSAL		The lamp in this product contains mercury. Please dispose of in accordance with local, state and federal laws.
POWER MANAGEMENT		Meets TCO'03 and ENERGY STAR® standards
PACKAGE CONTENTS		LCD display, VGA cable, power cable, audio cable, Quick Start Guide, ViewSonic Wizard CD
WARRANTY		Three-year limited warranty

ViewSonic®
See the difference® 

For more product information, visit us on the web at ViewSonic.com