VA712b

17" VALUE SERIES LCD DISPLAYS

WITH CLEARMOTIV™ 8MS VIDEO RESPONSE

Affordability without compromise.

The 17" ViewSonic® VA712b LCD display features ViewSonic's innovative CLEARMOTIV™ BROADCAST-QUALITY VIDEO COMBINED WITH DYNAMIC STRUCTURE™ TECHNOLOGY to deliver an 8ms video response that produces vibrant, clear images. This value-positioned display brings tech-savvy users all the bells and whistles they crave without the big price tag. OPTISYNC® TECHNOLOGY FURTHER ENHANCES THIS DISPLAY'S APPEAL by enabling connections to multiple digital and analog video sources. Enjoy a true multimedia experience with less clutter and fewer components on the desktop with the all-in-one VA712b LCD − great for mixed data, audio, graphics and video content.



FEATURE-RICH SOLUTION WITHOUT THE HIGH PRICE TAG

- > ClearMotiv 8ms video response time
 Ultra-fast 8ms video response delivers broadcast-quality
 full motion video
- Dynamic Structure technology Innovative liquid crystal composition and pixel matrix accelerate video response for seamless video and intense graphics.
- > OptiSync digital/analog inputs expand your connectivity Multi-mode input technology supports both digital (DVI) and analog (VGA) signals for ultimate compatibility and configuration flexibility.
- Multimedia enhanced Save desk and workspace and enjoy rich, stereo sound with two built-in stereo speakers.
- > Stylish slim-bezel design
 The full 17" viewable screen in an ultra-thin bezel lets you see more without taking up valuable desktop real estate.
- > Ultra-high 350 nit brightness (typ) and 350:1 contrast ratio (typ) for rich, detailed images
- > 1280x1024 resolution
- screen adjustability
 Screen adjustments are precisely
 made via an easy-to-use
 on-screen menu.

> OnView® controls for superior

- VESA® 75mm wall mount interface and Kensington® security port
- > PC and Mac® compatible
- > TCO'99 and ENERGY STAR® qualified



VA712b

17" VALUE SERIES LCD DISPLAY WITH CLEARMOTIV™ 8MS VIDEO RESPONSE





LCD	Туре	17" color TFT active matrix SXGA LCD
	Display Area	13.3" (horizontal) x 10.6" (vertical); 17.0" diagonal
	Optimum Resolution	on 1280x1024
	Contrast Ratio	350:1 (typ)
	Viewing Angles	176° horizontal, 173° vertical @ contrast ratio > 5:1
	Response Time	8ms (typ)
	Light Source	Long life, 50,000 hrs. (typ)
	Brightness	350 cd/m2 (typ)
	Panel Surface	Anti-glare
VIDEO INPUT	Analog/Digital	RGB analog (75 ohms, 0.7 Vp-p); DVI-D
	Frequency	F _h : 30~82kHz, F _v : 50~85Hz
	Sync	H/V separated (TTL)
COMPATIBILITY	PC	VGA up to 1280x1024 non-interlaced
	Mac®*	Power Mac™ G3/G4/G5 up to 1280x1024
CONNECTOR	Analog	15-pin mini D-sub, DVI-D
	Audio In	Stereo mini audio line in
	Power	3-pin AC plug
POWER	Voltage	AC 100–240V (universal), 50–60Hz (auto switch)
	Consumption	42W (typ)
AUDIO	Speakers	2x1-watt
	Amplifier	1-watt @ THD < 8%
CONTROLS	Basic	Power, 1, down, up, 2, mute
	OnView®	Auto image adjust, brightness, contrast, input selection,
		ViewMatch® color adjust (sRGB, 9300K, 6800K, 6500K),
		information (mode, model number, serial number), audio
		(volume, mute), manual image adjust (H. position, V. position,
		fine tune, sharpness), setup menu (language, resolution
		notice), OSD position, OSD timeout, OSD background,
		memory recall
OPERATING	Temperature	32-104°F (0-40°C)
CONDITIONS	Humidity	10–90% (non-condensing)
DIMENSIONS	Physical (mm)	386mm x 411mm x 177mm
(W x H x D)	Physical (in.)	15.2" x 16.2" x 7.0"
WEIGHT	Net	9.5 lb. (4.3 kg)
	Gross	15.0 lb. (6.8 kg)
REGULATIONS		UL, cUL, FCC-B, CB, CE, ENERGY STAR®, NOM, TUV/GS,
		TUV/ERGO, TUV-S (covers ISO13406-2 & MPR II), TCO'99,
		GOST-R + 20 original copies hygienic, SASO, PCBC, VCCI,
		BSMI, CCC, PSB, C-TICK, RoHS
POWER MANAGEMENT		Meets TCO'99 and ENERGY STAR® standards
PACKAGE CONTENTS		LCD display, video cable, power cable, AC adapter, audio
		cable, Quick Start Guide, ViewSonic Wizard
WARRANTY		Three-year limited warranty on parts, labor and backlight









ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.



the choice of professionals

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

Customer Service and Technical Support: (800) 688-6688 • Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

*Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2006 ViewSonic Corporation. All rights reserved. [12930-00B-04/06] VA712b-1