

VA930m

19" DIGITAL MEDIA HEIGHT ADJUST LCD

WITH CLEARMOTIV® 8MS VIDEO RESPONSE

Affordable, feature-rich display.

The ViewSonic® 19" VA930m is the ideal choice for students, small and home office, corporate and government users on a budget. It's packed with features not normally found in a value-priced display, including ERGONOMIC SWIVEL AND HEIGHT ADJUSTMENT that enhance productivity as you work in comfort. Graphics professionals and gamers will love the FAST 8MS VIDEO RESPONSE that brings broadcast-quality video and crystal-clear graphics to your desktop. OPTISYNC® ANALOG AND DIGITAL INPUTS ensure seamless compatibility with VGA and digital DVI sources. VESA® wall mount-compliance and INTEGRATED STEREO SPEAKERS reduce desktop clutter while accenting your office décor. The Kensington® security port offers theft deterrence and the OSD/Power lock ensures your optimal screen settings remain in place.



HIGH-END PERFORMANCE, ENTRY-LEVEL PRICING

- > **Stylish slim-bezel design**
The full 19" viewable screen in an ultra-thin bezel lets you see more without taking up valuable desktop real estate.
- > **Ergonomic base adds ease and comfort**
Ultimate ergonomic flexibility comes built-in with the convenient 3.2" height adjustment, tilt and 360° swivel.
- > **Multimedia enhanced**
Save workspace and enjoy rich, stereo sound with two built-in stereo speakers.
- > **ClearMotiv® 8ms video response time**
Fast 8ms video response delivers broadcast-quality video.
- > **Dynamic Structure™ technology**
Innovative liquid crystal composition and pixel matrix accelerate video response for seamless video and intense graphics.
- > **OptiSync® digital/analog inputs expand your connectivity**
Multi-mode input technology supports both digital (DVI) and analog (VGA) signals for ultimate compatibility and configuration flexibility.
- > **High 300 nit brightness (typ) and 700:1 contrast ratio (typ)**
- > **Windows Vista approved**
- > **PC and Mac® compatible**
- > **TCO'03 and ENERGY STAR® qualified**



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

ViewSonic®
See the difference® 

VA930m

19" DIGITAL MEDIA HEIGHT ADJUST LCD WITH CLEARMOTIV® 8MS VIDEO RESPONSE



360° SWIVEL



HEIGHT ADJUST



TILT



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

Customer Service and Technical Support: (800) 688-6688 • Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

*Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Windows Vista and the Windows logo are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2007 ViewSonic Corporation. All rights reserved. [13367-00B-01/07] VA930m-1

LCD	Type	19" color TFT active matrix SXGA LCD
	Display Area	14.8" horizontal x 11.9" vertical; 19.0" diagonal
	Optimum Resolution	1280x1024
	Contrast Ratio	700:1 (typ)
	Viewing Angles	160° horizontal, 155° vertical @ contrast ratio > 5:1
	Response Time	8ms (typ)
	Light Source	Long life, 50,000 hrs. (typ)
	Brightness	300 cd/m2 (typ)
	Panel Surface	Anti-glare
VIDEO INPUT	Analog/Digital	RGB analog (75 ohms, 0.7 Vp-p)/DVI-D
	Frequency	F _H : 30~82kHz, F _V : 50~75Hz
	Sync	H/V separated (TTL)
COMPATIBILITY	PC	VGA up to 1280x1024 non-interlaced
	Mac**	Power Mac™ G3/G4/G5 up to 1280x1024
CONNECTOR	Analog/Digital	15-pin mini D-sub/DVI-D
	Audio In	Stereo mini audio line in
	Power	3-pin AC plug
POWER	Voltage	AC 100~240V (universal), 50~60Hz (auto switch)
	Consumption	35W (typ)
AUDIO	Speakers	2x1.5-watt
	Amplifier	1.5-watt
CONTROLS	Basic	Power, 1, down, up, 2, mute, volume +/-
	OnView®	Auto image adjust, brightness, contrast, input selection, ViewMatch® color adjust (sRGB, 9300K, 6800K, 6500K), information (mode, model number, serial number), audio (volume, mute), manual image adjust (H. position, V. position, fine tune, sharpness), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), memory recall
ERGONOMICS		Height adjustment range 3.2", tilt, swivel range 360°
OPERATING CONDITIONS	Temperature	41~95°F (5~35°C)
	Humidity	20~80% (non-condensing)
DIMENSIONS (W x H x D)	Physical with stand	16.8" x 18.9" x 9.06" (428mm x 479mm x 230mm)
	Physical without stand	16.8" x 15.5" x 2.6" (428mm x 393.7mm x 66mm)
WEIGHT	Net with stand	13.3 lb. (6.0 kg)
	Net without stand	9.9 lb. (4.5 kg)
	Gross with stand	16.0 lb. (7.2 kg)
REGULATIONS		UL, cUL, FCC-B, CB, CE, ENERGY STAR®, NOM, TUV/GS, TUV-S, TUV/ERGO (covers ISO13406-2 & MPR II), TCO'03, GOST-R + 20 original copies hygienic, SASO, PCBC, VCCI, BSMI, CCC, PSB, C-TICK, RoHS
RECYCLE/DISPOSAL		The lamp in this product contains mercury. Please dispose of in accordance with local, state and federal laws.
POWER MANAGEMENT		Meets TCO'03 and ENERGY STAR® standards
PACKAGE CONTENTS		LCD display, VGA cable, power cable, audio cable, Quick Start Guide, ViewSonic Wizard CD
WARRANTY		Three-year limited warranty

ViewSonic®
See the difference® 

For more product information, visit us on the web at ViewSonic.com