

# VG1930wm

## 19" WIDESCREEN GRAPHIC SERIES LCD

WITH SWIVEL AND HEIGHT ADJUST

## Big screen, big performance.

The ViewSonic® 19" VG1930wm features widescreen and multimedia performance for a unique desktop experience. Ideal for use by graphics professionals who need the wider screen area to see all their work and for working in two documents side-by-side. Gamers and graphics professionals will love the FAST 5MS VIDEO RESPONSE that delivers blur-free, full motion video and crystal-clear graphics rendering. OPTISYNC® ANALOG AND DIGITAL INPUTS provide versatile connectivity options. The INTEGRATED AMP AND STEREO SPEAKERS give you a complete multimedia experience and the attractive slim bezel is VESA® wall mount-compliant so you can accent your office décor and make the most of valuable desktop space. Choose the VG1930wm widescreen multimedia display for a complete visual display experience on your desktop.



### FAST, WIDESCREEN DISPLAY

- > **ClearMotiv® 5ms video response time**  
Fast 5ms video response delivers broadcast-quality video.
- > **Dynamic Structure™ technology**  
Innovative liquid crystal composition and pixel matrix accelerate video response for seamless video and intense graphics.
- > **OptiSync® digital/analog inputs expand your connectivity**  
Multi-mode input technology supports both digital (DVI) and analog (VGA) signals for ultimate compatibility and configuration flexibility.
- > **Ergonomic base adds ease and comfort**  
Ultimate ergonomic flexibility comes built-in with the convenient 3.2" height adjustment and 360° swivel.
- > **Multimedia enhanced**  
Save workspace and enjoy rich, stereo sound with two built-in stereo speakers.
- > **Stylish slim-bezel design**  
The full 19" viewable widescreen in an ultra-thin bezel lets you see more without taking up valuable desktop real estate.
- > **High 300 nit brightness (typ) and 700:1 contrast ratio (typ)**
- > **VESA® 75mm wall mount interface and Kensington® security port**
- > **Windows Vista approved**
- > **PC and Mac® compatible**
- > **TCO'03 and ENERGY STAR® qualified**



**VIEWSONIC**  
PRODUCTS, PROGRAMS,  
AND SERVICES

**ViewSonic®**  
See the difference® 

# VG1930wm

19" WIDESCREEN GRAPHIC SERIES LCD WITH SWIVEL AND HEIGHT ADJUST



360° SWIVEL



HEIGHT ADJUST



TILT



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

<b>LCD</b>	Type	19" color TFT active matrix SXGA+ LCD
	Display Area	16.1" horizontal x 10.1" vertical; 19" diagonal
	Optimum Resolution	1440x900
	Contrast Ratio	700:1 (typ)
	Viewing Angles	160° horizontal, 160° vertical @ contrast ratio > 10:1
	Response Time	5ms (typ)
	Light Source	Long life, 50,000 hrs. (typ)
	Brightness	300 cd/m2 (typ)
	Panel Surface	Anti-glare
<b>VIDEO INPUT</b>	Analog/Digital	RGB analog (75 ohms, 0.7 Vp-p)/DVI-D
	Frequency	F <sub>H</sub> : 24~82kHz, F <sub>V</sub> : 50~75Hz
	Sync	H/V separated (TTL)
<b>COMPATIBILITY</b>	PC	VGA up to 1440x900 non-interlaced
	Mac**	Power Mac™ G3/G4/G5 up to 1440x900
<b>CONNECTOR</b>	Analog/Digital	15-pin mini D-sub/DVI-D
	Audio In	Stereo mini audio line in
	Power	3-pin AC plug
<b>POWER</b>	Voltage	AC 100–240V (universal)
	Consumption	35W (typ)
<b>AUDIO</b>	Speakers	2x1.5-watt
	Amplifier	1.5-watt @ THD < 8%
<b>CONTROLS</b>	Basic	Power, 1, down, up, 2, mute, volume +/-
	OnView®	Auto image adjust, brightness, contrast, input selection, ViewMatch® color adjust (sRGB, 9300K, 6800K, 6500K), information (mode, model number, serial number), audio (volume, mute), manual image adjust (H. position, V. position, fine tune, sharpness), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), memory recall
<b>ERGONOMICS</b>		Height adjustment range 3.2", tilt, swivel range 360°
<b>OPERATING</b>	Temperature	41–95°F (3–35°C)
<b>CONDITIONS</b>	Humidity	20–80% (non-condensing)
<b>DIMENSIONS</b>	Physical with stand	18.1" x 17.1" x 9.1" (460mm x 434mm x 230mm)
	Physical without stand	18.1" x 13.9" x 2.4" (460mm x 352mm x 61mm)
<b>WEIGHT</b>	Net with stand	11.9 lb. (5.4 kg)
	Net without stand	9.6 lb. (4.4 kg)
	Gross with stand	15.2 lb. (6.9 kg)
<b>REGULATIONS</b>		UL, cUL, FCC-B, ICES-003, CB, CE, ENERGY STAR®, NOM, TUV/GS, Argentina TUV-S, TUV/ERGO (covers ISO13406-2 & MPR II), TCO'03, GOST-R, SASO, PCBC, VCCI, BSMI, CCC, MIC, PSB, C-TICK, RoHS
<b>RECYCLE/DISPOSAL</b>		The lamp in this product contains mercury. Please dispose of in accordance with local, state and federal laws.
<b>POWER MANAGEMENT</b>		Meets TCO'03 and ENERGY STAR® standards
<b>PACKAGE CONTENTS</b>		LCD display, VGA cable, power cable, audio cable, Quick Start Guide, ViewSonic Wizard CD
<b>WARRANTY</b>		Three-year limited warranty

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

Customer Service and Technical Support: (800) 688-6688 • Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

\*Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Windows Vista and the Windows Vista logo are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2007 ViewSonic Corporation. All rights reserved. [13349-00B-01/07] VG1930wm-1

**ViewSonic®**  
See the difference®

For more product information, visit us on the web at [ViewSonic.com](http://ViewSonic.com)