

## Bring your music, videos and photos together.

ViewSonic's 19" VX1945wm ViewDock™ LCD blasts through barriers with its INNOVATIVE FUNCTIONALITY and beautiful piano-black, gloss finish. Dock your iPod® and listen to tunes while you surf the Internet or do your work. You can even DOWNLOAD MUSIC DIRECTLY TO YOUR IPOD on the ViewDock. Defend against all comers in your games with no blurs, ghosting or jaggies to slow you down. Feel the sound with the INTEGRATED STEREO SPEAKERS AND SUBWOOFER driving unprecedented audio richness to your desktop display. The VX1945wm sets new standards in multimedia displays with an 8-in-1 card reader,\* USB connection for your joystick/game control, integrated microphone and headphone jack. Your desktop experience will never be the same once you bring it all together with your VX1945wm ViewDock and iPod.

# VX1945wm

## 19" WIDESCREEN VIEWDOCK™ LCD

WITH IPOD® DOCK IN MULTIMEDIA BASE



### HIGH-PERFORMANCE VIDEO AND IPOD COMBINED

- > **Multimedia base with iPod dock**  
Multimedia base features iPod dock, 8-in-1 card reader, microphone, headphone jack, four USB ports for joystick/game control, keyboard/mouse and more.
- > **Full 19" viewable widescreen with 1440x900 resolution**
- > **ClearMotiv® 5ms video response time**  
Fast 5ms video response enables digital, HD broadcast-quality video.
- > **Stylish slim-bezel design with glossy, piano-black finish**  
The thin bezel lets you see more without taking up valuable desktop real estate. The high neck and floating head design accentuate the visual experience.
- > **Dynamic Structure™ technology**  
Innovative liquid crystal composition and pixel matrix accelerate video response for seamless video and intense graphics.
- > **OptiSync® digital/analog inputs expand your connectivity**  
Multi-mode input technology supports both digital (DVI) and analog (VGA) signals for ultimate compatibility and configuration flexibility.
- > **Ultra-high brightness and contrast**  
300-nit brightness (typ) and 700:1 contrast ratio (typ) for rich, detailed images.
- > **Windows Vista approved**
- > **PC and Mac® compatible**
- > **MPR II and ENERGY STAR® qualified**

**5ms**



**VIEWSONIC**  
PRODUCTS, PROGRAMS,  
AND SERVICES

**ViewSonic®**  
See the difference® 

# VX1945wm

19" WIDESCREEN LCD WITH IPOD® DOCK IN MULTIMEDIA BASE



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

Customer Service and Technical Support: (800) 688-6688 • Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

\*Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Windows Vista and the Windows Vista logo are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2007 ViewSonic Corporation. All rights reserved. [13360-00B-01/07] VX1945wm-1

<b>LCD</b>	Type	19" Wide Color TFT Active Matrix LCD
	Display Area	16.1" horizontal x 10.0" vertical; 19" diagonal
	Optimum Resolution	1440x900
	Contrast Ratio	700:1 (typ)
	Viewing Angles	160° horizontal, 160° vertical @ contrast ratio > 10:1
	Response Time	5ms (typ)
	Light Source	Long life, 40,000 hrs. (typ)
	Brightness	300 cd/m2 (typ)
	Panel Surface	Anti-glare
<b>VIDEO INPUT</b>	Analog/Digital	RGB analog (75 ohms, 0.7 Vp-p)/DVI-D (TMDS, 100 ohms)
	Frequency	F <sub>H</sub> : 30~82kHz, F <sub>V</sub> : 50~85Hz
	Sync	H/V separated (TTL), composite, sync-on-green
<b>COMPATIBILITY</b>	PC	VGA up to 1440x900 non-interlaced
	Mac**	Power Mac™ G3/G4/G5 up to 1440x900
<b>CONNECTOR</b>	Analog/Digital	15-pin mini D-sub/DVI-D
	Power	3-pin AC plug (CEE22)
	Base	iPod dock, USB (A type)x4, USB (B type)x1, audio out stereo jack, 2-in-1 audio in, headphone jack
<b>AUDIO</b>	Speakers	2x2-watt
	Sub-woofer	1x3-watt
<b>POWER</b>	Voltage	AC 100–240V, 50–60Hz (auto switch)
	Consumption	59W (typ)
<b>CONTROLS</b>	Basic	Power, 1, down, up, 2, sub volume
	OnView®	Auto image adjust, brightness, contrast, input select (analog, digital), ViewMatch® color adjust (sRGB, 9300K, 6500K-default, 5400K, user color - RGB), information (resolution, H. frequency, V. frequency, pixel clock, model number, serial number), manual image adjust (H. size, H. position, V. position, fine tune, sharpness), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), memory recall
<b>OPERATING CONDITIONS</b>	Temperature	41–95°F (5–35°C)
	Humidity	20–80% (non-condensing)
<b>DIMENSIONS (W x H x D)</b>	Physical with stand	17.7" x 17" x 8.4" (450mm x 449mm x 212mm)
	Physical without stand	17.7" x 13.4" x 2.6" (450mm x 341mm x 65.5mm)
<b>WEIGHT</b>	Net with stand	12.6 lb. (5.7 kg)
	Net without stand	9.6 lb. (4.4 kg)
	Gross with stand	17 lb. (7.7 kg)
<b>REGULATIONS</b>		UL, cUL, FCC-B, CB, CE, ENERGY STAR®, NOM, NEMKO/GS (covers TUV/GS), NEMKO ERGO (covers TUV/ERGO, ISO13406-2 & MPR II), MPR II, GOST-R + 20 original copies hygienic, SASO, PCBC, VCCI, BSMI, CCC, PSB, C-TICK, Argentina-S, Green Mark, RoHS
<b>RECYCLE/DISPOSAL</b>		The lamp in this product contains mercury. Please dispose of in accordance with local, state and federal laws.
<b>POWER MANAGEMENT</b>		Meets MPR II and ENERGY STAR® standards
<b>PACKAGE CONTENTS</b>		LCD display, power cable, 15-pin VGA video cable, DVI cable, Quick Start Guide, ViewSonic Wizard CD
<b>WARRANTY</b>		Three-year limited warranty on LCD, parts and labor.

**ViewSonic®**  
See the difference®

For more product information, visit us on the web at [ViewSonic.com](http://ViewSonic.com)