

ViewSonic®

VX500 LCD Display



High-tech and high-style converge with this 15" LCD display.

Sculpted with a modern silver and black bezel, this 15" LCD display combines technical sensibility with stylish ingenuity. Its sleek design and ultra-thin profile make it ideal for professionals with limited workspace. ViewSonic's exclusive OptiSync™ digital/analog multi-mode input technology supports both digital and analog signals for ultimate compatibility and configuration flexibility. And its multimedia functionality, including built-in speakers and integrated microphone, make the VX500 ideal for office applications, computer training and videoconferencing.

- **OPTISYNC™ technology**
BEYOND DIGITAL™
This multi-mode input technology supports both digital (DVI) and analog (VGA) signals. The digital interface delivers optimized image quality with minimum adjustment for ultimate configuration flexibility.
- **Full 15" viewable screen**
Equivalent to a 17" CRT monitor.
- **1024x768 native resolution**
- **Bezel integrated speakers**
The two 2-watt built-in audio speakers save desk and work space while offering superior sound quality.
- **Touch-sensitive digital controls**
Sleek, metallic soft-touch buttons utilize capacitive sensors to respond to the slightest touch for easy adjustments.
- **Asset management**
Conforms to industry standards for remote identification in an enterprise networked environment.
- **ViewSonic Wizard**
This software provides user-friendly installation. The included CD-ROM automates the set-up process to deliver optimized screen performance.
- **Built-in microphone**
Allows bi-directional communications in true multimedia applications such as video conferencing and computer telephony.



ViewSonic®
See the difference.®

ViewSonic®

VX500 LCD Display



- **OSD/Power lock function**

When activated, the user-controlled OSD/Power lock function prevents changes to monitor settings, maintaining an optimized image.

- **Elegant silver-on-black design**

The graceful design complements both home and office computing environments.

- **TCO'99 and ENERGY certified**

- **Three-year limited warranty**

- **Give your desktop a signature look**

ViewSonic has a wide variety of accessories for your LCD, including stylish multifunctional keyboards and video solutions. For a complete accessories list, visit ViewSonic.com.



Keyboard sold separately.

15.0" TFT LCD DISPLAY

LCD PANEL	Type Display Area Optimum Resolution Contrast Ratio Viewing Angles Response Time Light Source Brightness Panel Surface	15.0" color TFT active matrix 12.0" (horizontal) x 9.0" (vertical); 15.0" diagonal 1024x768 400:1 (typ) 120° horizontal, 100° vertical (typ) 30ms (typ) Long life, 50,000 hrs. (typ) 300 cd/m ² (typ) Anti-glare
VIDEO INPUT	Analog Digital Frequency Sync	RGB Analog (75 ohms, 0.7/1.0 Vp-p) DVI-D (TMDS, 100 ohms) F _H : 30~62kHz; F _V : 50~85Hz H/V Separated (TTL), composite, sync-on-green
COMPATIBILITY	PC Mac ®*	VGA up to 1024x768 non-interlaced Power Mac™ G3/G4 up to 1024x768
CONNECTOR	Analog Digital Power Audio	15-pin mini D-sub Digital DVI-D 3-pin AC Plug (CEE22) 3.5mm audio line-in
AUDIO	Speakers Amplifier	2 x 2-watts 2-watts at 1KHz
POWER	Voltage Consumption	AC 100~240V, 50~60Hz (auto switch) 38W (typ), <3W (standby)
CONTROLS	Basic OnView ®	Power, 1, down, up, 2, mute, volume (+, -) Auto image adjust, contrast, brightness, input select, ViewMatch® color adjust (9300K, 6500K-default, 5400K, 5000K, RGB), audio adjust (volume, balance, bass, treble, mute), information (resolution, model number, serial number, website), manual image adjust (H. size, H/V position, fine tune, sharpness), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), memory recall
OPERATING CONDITIONS	Temperature Humidity	32° F~104° F (0° C~40° C) 10%~90% (non-condensing)
DIMENSIONS (W x H x D)	Physical	360.0mm x 342.0mm x 139.5mm (14.2" x 13.5" x 5.5")
WEIGHT	Net Gross	8.6 lbs. (3.9 kgs) 13.0 lbs. (5.9 kgs)
REGULATIONS		UL, c-UL, IC-B, CB Report, CE, FCC-B, TUV/Ergo, ISO13406-2, TUV/GS, SEMKO, DEMKO, FIMKO, NEMKO, BSMI, VCCI, PSB, PCBC, TUV-S, TCO'99, EPA, NOM, C-TICK, GOST-R, PCT (BZ02), CCC, ENERGY STAR®
POWER MANAGEMENT		Meets TCO'99 and ENERGY standards
WARRANTY		Three-year limited warranty on parts, labor and backlight.



ISO 9001:2000
FM 40187



ISO 14001:1996
FM 40968

ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.



ViewSonic®
See the difference.™

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789
Phone (800) 888-8583 or (909) 444-8888 • In Canada (866) 262-1967 • Fax (909) 839-7922 • SalesInfo@ViewSonic.com • ViewSonic.com

*Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2003 ViewSonic Corporation. All rights reserved. [10381-05B-07/03] VX500-2